


# SUS304配管パイプ

SUS304TP-A



1本の質量(kg/本)

外径 D mm	呼び径		肉 厚 t mm 定尺4,000mm(一部6,000mmあり)										
	A	B	1.5	2.0	2.5	3.0	3.5	4.0	5.0	5.2	5.5	6.0	6.5
10.5	6	1/8	1.34	1.69									
13.8	8	1/4	1.84	2.35		3.23							
17.3	10	3/8	2.36	3.05	3.69	4.28							
21.7	15	1/2	3.02	3.92	4.80	5.60							
27.2	20	3/4	3.84	5.04	6.16	7.24							
34.0	25	1	4.84	6.36	7.84	9.28	10.6	12.0					
42.7	32	1 1/4	6.16	8.12	10.00	11.9	13.7	15.4					
48.6	40	1 1/2	7.04	9.28		13.6	15.7	17.8					
60.5	50	2	8.80	11.60		17.2	19.9	22.5	27.6		30.2		
76.3	65	2 1/2		14.80		21.9	25.4	28.8	35.5	36.8		42.0	
89.1	80	3		17.40		25.7		33.9	42.0		46.0	49.6	
101.6	90	3 1/2		19.80		29.5		38.9	48.0			57.2	
114.3	100	4		22.40		33.3		44.0	54.4			64.8	
139.8	125	5		27.50		40.8	47.6	54.0	67.2			80.0	
165.2	150	6				48.4	56.4	64.4	80.0			95.2	
216.3	200	8				63.6		84.8	105.0			126.0	136.0
267.4	250	10				79.2	92.0	105.0	131.0			156.0	169.0
318.5	300	12				94.4		125.0	156.0			187.0	202.0
355.6	350	14						140.0	175.0			209.0	
406.4	400	16						161.0	201.0			240.0	
457.2	450	18						181.0	226.0			270.0	

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。重量を表示している規格は標準在庫品です。