


# ステンレス等辺アングル(304/316/316L/430) 1

SUS304/316/316L/430(熱間圧延品)




■ 全面HL、外2面#400研磨もあり    ○ 外2面#400研磨もあり    △ 全面HL研磨もあり    1本の質量(Kg/本)

寸法 mm		304			316・316L		430
辺 A	厚さ t	定尺長さ mm			定尺長さ mm		定尺長さ mm
		4,000	5,000	6,000	4,000	6,000	4,000
20	3	■ 3.58			3.60		○ 3.47
25	3	■ 4.52			4.56		○ 4.40
30	2						○ 3.62
	3	■ 5.48	6.85	■ 8.22		8.28	○ 5.32
	4			10.6			
	5			13.1			
	6			15.2			
35	3			9.66			
	4	8.40		12.6			
	6			18.2			
40	2						○ 4.88
	3	■ 7.40	9.25	■ 11.1		11.2	○ 7.20
	4	■ 9.64		■ 14.5			
	5	△ 11.9	14.9	■ 17.9		18.0	
	6	14.0		△ 21.0			
45	4			16.6			
	5			20.5			
50	3	△ 9.48		△ 14.2			
	4	△ 12.4	15.4	■ 18.5		18.7	
	5	△ 15.2	19.0	■ 22.9		23.0	
	6	△ 17.9	22.4	■ 26.9		27.0	
	8			34.7			
	9	25.8		△ 38.6			
60	5			27.6			
	6			■ 32.6			
65	5			30.3			
	6	△ 23.9	29.8	■ 35.8		36.1	
	8			46.4			
	9			51.8			

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

# ステンレス等辺アンクル(304/316/316L/430) 2

SUS304/316/316L/430(熱間圧延品)



■ 全面HL、外2面#400研磨もあり

△ 全面HL研磨もあり

1本の質量(Kg/本)

寸法 mm		304			316・316L		430
辺 A	厚さ t	定尺長さ mm			定尺長さ mm		定尺長さ mm
		4,000	5,000	6,000	4,000	6,000	4,000
70	5			32.7			
	7			44.5			
75	5			35.0			
	6	△ 27.7	34.6	■ 41.5		41.8	
	8			54.1			
	9	△ 40.4		■ 60.6		60.6	
80	6			44.4			
	8			△ 57.8			
	10			70.8			
90	6			50.2			
	8			66.0			
	9	49.2		△ 73.8			
	10			81.0			
	12			96.0			
100	6	37.3	46.6	■ 55.9			
	8	48.8		△ 73.2			
	9			82.2			
	10	△ 60.4		■ 90.6		91.2	
	12			107.0			
125	9			103.0			
	12			136.0			
	15			167.0			
130	12			142.0			
150	9			125.0			
	12			165.0			
	15			203.0			

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。





