


ステンレスチャンネル(304/316/316L)

SUS304(熱間圧延品・溶接品)316/316L(溶接品)

○ 溶接品

△ 6M圧延品、4M溶接品

1本の質量(Kg/本)



寸法 mm			304		316・316L	R1	R2
縦 H	横 B	肉厚 t	定尺長さ mm		定尺長さ mm		
			4,000	6,000	6,000		
40	20	3.0		10.8		4.0	2.0
50	25	3.0		13.7		4.0	2.0
80	40	3.0		○ 22.3		4.5	2.0
	40	5.0	24.0	35.9	36.1	4.5	3.0
100	50	3.0		○ 28.5		6.5	2.0
	50	4.0	24.8	37.2	37.4	6.5	3.0
	50	5.0	30.6	45.9	46.2	6.5	3.0
	50	6.0	36.1	54.1	54.4	6.5	4.5
120	60	6.0		○ 65.4		6.5	4.0
130	65	6.0	48.0	72.0	72.6	8.5	4.0
150	75	6.0	55.6	83.4	84.0	8.5	4.0
	75	9.0	81.2	122.0	122.0	8.5	6.0
200	100	6.0	○ 74.8	○ 112.0		10.0	5.0
	100	8.0	○ 98.4	○ 148.0		10.0	6.0
	100	10.0	△ 121.0	△ 182.0	△ 183.0	10.0	7.0

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。