


SUS304フラットバー 1

SUS304 FB HOT/ COLD/HL/#400研磨




スリットの酸洗肌

寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400		
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間	スリット
2	6	2,000	0.190			○			3	38	4,000	3.62	<input type="checkbox"/>	○	○	○	○		
	8	"	0.254			○				40	"	3.81	<input type="checkbox"/>	○	○	○	○	○	
	9	"	0.286			○				42	"	4.00			○	○			
	10	"	0.318			○				45	"	4.28	<input type="checkbox"/>	○	○	○	○		
	10	3,000	0.477							48	"	4.56			○	○			
	10	4,000	0.636		○	○	○			50	"	4.76	<input type="checkbox"/>	○	○	○	○	○	○
	12	"	0.760			○				60	"	5.72	<input type="checkbox"/>	○	○	○	○	○	○
	15	"	0.952		○	○	○			65	"	6.20	<input type="checkbox"/>	○	○	○	○		
	20	"	1.27		○	○	○			75	"	7.12		○	○	○	○	○	○
	25	"	1.58		○	○	○			90	"	8.56			○				
	30	"	1.90		○	○	○			100	"	9.52		○	○	○	○	○	○
	32	"	2.03		○	○	○			110	"	10.5			○				
	35	"	2.22		○					120	"	11.4			○				
	38	"	2.41		○	○				125	"	11.9			○				
	40	"	2.54		○	○	○			130	"	12.4			○				
45	"	2.86		○	○	○		140	"	13.3			○						
50	"	3.17		○	○	○		150	"	14.3			○						
3	5	3,000	0.357			○			4	9	"	1.14			○				
	6	4,000	0.572			○				10	"	1.27			○	○			
	7	"	0.668			○				11	"	1.40		○	○	○			
	8	"	0.760			○				12	"	1.52			○				
	9	"	0.856			○				13	"	1.65		○	○	○			
	10	"	0.952		○	○	○			15	"	1.90	○	○	○	○	○	○	
	12	"	1.14	<input type="checkbox"/>	○	○	○			16	"	2.03	○	○	○	○	○		
	13	"	1.24		○	○	○			17	"	2.16			○				
	15	"	1.43	<input type="checkbox"/>	○	○	○	○		19	"	2.41	○	○	○	○	○		
	16	"	1.52		○	○	○			20	"	2.54	○	○	○	○	○	○	
	19	"	1.81	<input type="checkbox"/>	○	○	○			22	"	2.79	○	○	○	○	○		
	20	"	1.90	<input type="checkbox"/>	○	○	○	○		25	"	3.17	○	○	○	○	○	○	
	22	"	2.09		○	○	○			30	"	3.81	○	○	○	○	○	○	
	25	"	2.38	<input type="checkbox"/>	○	○	○	○		32	"	4.08	○	○	○	○	○	○	
	30	"	2.86	<input type="checkbox"/>	○	○	○	○		35	"	4.44	○	○	○	○	○		
32	"	3.04	<input type="checkbox"/>	○	○	○	○	38	"	4.84	○	○	○	○	○	○			
35	"	3.33	<input type="checkbox"/>	○	○	○		40	"	5.08	○	○	○	○	○	○			

SUS304フラットバー 2


SUS304 FB HOT/ COLD/HL/#400研磨



寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400		
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間	スリット
4	45	4,000	5.72	○	○	○	○		6	10	4,000	1.90			○	○			
	50	"	6.36	○	○	○	○	○		12	"	2.28			○	○			
	60	"	7.60	○	○	○	○	○		13	"	2.48			○	○			
	65	"	8.24	○	○	○	○			15	"	2.86	○	○	○	○	○	○	
	75	"	9.52	○	○	○	○	○		16	"	3.04			○	○			
	90	"	11.4			○	○			18	"	3.42			○	○			
	100	"	12.7		○	○	○	○		19	"	3.62	○	○	○	○			
5	8	"	1.27			○			20	"	3.81	○	○	○	○	○	○		
	9	"	1.43			○			22	"	4.20	○	○	○	○				
	10	"	1.59			○	○		25	"	4.76	○	○	○	○	○	○		
	12	"	1.90			○	○		25	5,000	5.95	○							
	13	"	2.06			○	○		25	6,000	7.14	○							
	15	"	2.38	○	○	○	○	○	30	4,000	5.72	○	○	○	○	○	○		
	16	"	2.54			○	○		30	5,000	7.15	○							
	19	"	3.01	○	○	○	○		30	6,000	8.58	○				○			
	20	"	3.17	○	○	○	○	○	32	4,000	6.08	○	○	○	○	○	○		
	22	"	3.49	○	○	○	○		32	5,000	7.60	○							
	25	"	3.96	○	○	○	○	○	32	6,000	9.12	○							
	30	"	4.76	○	○	○	○	○	35	4,000	6.68	○	○	○	○				
	32	"	5.08	○	○	○	○	○	38	"	7.24	○	○	○	○	○	○		
	34	"	5.40			○	○		38	5,000	9.05	○							
	35	"	5.56	○	○	○	○		38	6,000	10.9	○	○			○			
	38	"	6.04	○	○	○	○	○	40	4,000	7.6	○	○	○	○	○	○		
	40	"	6.36	○	○	○	○	○	40	5,000	9.5	○							
	45	"	7.12	○	○				40	6,000	11.4	○				○			
	50	"	7.92	○	○	○	○	○	42	4,000	8.00				○	○			
	60	"	9.52	○	○	○	○	○	45	"	8.56	○	○	○	○	○	○	○	
	65	"	10.3	○	○	○	○	○	48	"	9.12	○	○	○	○	○			
75	"	11.9	○	○	○	○	○	50	"	9.52	○	○	○	○	○	○	○		
90	"	14.3	○	○	○	○		50	5,000	11.9	○								
100	"	15.8	○	○	○	○	○	50	6,000	14.3	○	○			○				
130	"	20.6			○			60	4,000	11.4	○	○	○	○	○	○	○		
150	"	23.8			○			65	"	12.4	○	○	○	○	○	○	○		
6	9	"	1.71			○			65	5,000	15.4	○							

SUS304フラットバー 3


SUS304 FB HOT/ COLD/HL/#400研磨



寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400		
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間	スリット
6	65	6,000	18.5	○	○		○		9	22	4,000	6.28	○	○	○	○			
	70	4,000	13.3	○	○	○	○			25	"	7.12	○	○	○	○	○		
	75	"	14.3	○	○	○	○	○		25	6,000	10.7			○				
	75	5,000	17.8	○						30	4,000	8.56	○	○	○	○	○	○	
	75	6,000	21.4	○	○		○			30	6,000	12.8			○				
	90	4,000	17.1	○	○	○	○			32	4,000	9.12	○	○	○	○	○	○	
	100	"	19.0	○	○	○	○	○		32	5,000	11.4	○						
	100	5,000	23.8	○						32	6,000	13.7	○		○				
	100	6,000	28.6	○	○		○			35	4,000	10.0	○		○	○			
	110	4,000	20.9		○	○	○			38	"	10.8	○	○	○	○	○	○	○
	120	"	22.8		○	○	○			38	5,000	13.6	○						
	125	"	23.8		○	○	○			38	6,000	16.3	○		○				
	130	"	24.8		○	○	○			40	4,000	11.4	○	○	○	○	○	○	○
	140	"	26.6		○	○	○			40	5,000	14.2	○						
150	"	28.6		○	○	○		40	6,000	17.1	○		○						
7	20	"	4.44	○				45	4,000	12.8	○	○	○						
8	10	"	2.54			○	○		50	"	14.3	○	○	○	○	○	○		
	16	"	4.08	○		○	○		50	5,000	17.8	○							
	25	"	6.36	○					50	6,000	21.4	○	○	○					
	30	"	7.60	○					55	4,000	15.7	○							
	32	"	8.12	○		○	○	○	60	"	17.1	○	○	○	○	○	○		
	35	"	8.88	○					65	"	18.6	○	○	○	○	○	○		
	38	"	9.64	○		○	○		65	5,000	23.2	○							
	40	"	10.2	○					65	6,000	27.8	○	○	○					
	45	"	11.4	○					75	4,000	21.4	○	○	○	○	○	○		
	50	"	12.7	○		○	○		75	5,000	26.8	○							
	65	"	16.5	○					75	6,000	32.1	○	○	○					
9	75	"	19.0	○					90	4,000	25.7	○	○	○	○				
	100	"	25.4	○					90	5,000	32.1	○							
	13	"	3.71	○		○	○		90	6,000	38.5	○							
	15	"	4.28	○		○	○	○	100	4,000	28.6	○	○	○	○	○	○		
	16	"	4.56	○		○	○		100	5,000	35.7	○							
	19	"	5.44	○		○	○		100	6,000	42.8	○	○	○					
20	"	5.72	○	○	○	○	○	125	4,000	35.7	○		○	○					

SUS304フラットバー 4


SUS304 FB HOT/ COLD/HL/#400研磨



寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間
9	125	5,000	44.6	○					12	14	4,000	5.32			○			
	125	6,000	53.5	○						15	"	5.72	○					
	150	4,000	42.8	○		○	○			16	"	6.08			○	○		
	150	5,000	53.5	○						19	"	7.24	○		○	○		
	150	6,000	64.2	○						20	"	7.60	○		○	○	○	
	200	4,000	57.2	○		○	○			25	"	9.52	○		○	○	○	
	250	"	71.2	○		○	○			25	6,000	14.3			○			
	300	"	85.6	○		○				30	4,000	11.4	○		○	○	○	
10	15	"	4.76	○		○	○	○	30	6,000	17.1			○				
	19	"	6.04	○		○	○		32	4,000	12.2	○		○	○	○		
	20	"	6.36	○		○	○	○	32	6,000	18.3			○				
	25	"	7.92	○		○	○	○	35	4,000	13.3	○		○				
	30	"	9.52	○		○	○	○	38	"	14.5	○		○	○	○		
	32	"	10.2	○		○	○	○	38	5,000	18.1	○						
	35	"	11.1	○					38	6,000	21.7	○		○				
	38	"	12.0	○		○	○	○	40	4,000	15.2	○		○	○	○		
	40	"	12.7	○		○	○	○	40	6,000	22.9			○				
	45	"	14.3	○					45	4,000	17.1	○						
	50	"	15.8	○		○	○	○	50	"	19.0	○		○	○	○		
	50	5,000	19.8	○					50	5,000	23.8	○						
	50	6,000	23.8	○		○			50	6,000	28.6	○		○				
	60	4,000	19.0	○					65	4,000	24.8	○		○	○	○		
	65	"	20.6	○		○	○	○	65	5,000	31.0	○						
	65	6,000	30.9	○		○			65	6,000	37.1	○		○				
	75	4,000	23.8	○		○	○		70	4,000	26.6	○						
	75	6,000	35.7			○			75	"	28.6	○		○	○	○		
	100	4,000	31.7	○		○	○	○	75	5,000	35.7	○						
	100	5,000	39.6	○					75	6,000	42.8	○		○				
	100	6,000	47.6	○		○			90	4,000	34.2	○		○	○			
	125	4,000	39.6	○		○	○		100	"	38.1	○		○	○	○		
	150	"	47.6	○		○	○		100	5,000	47.6	○						
	200	"	63.6	○		○	○		100	6,000	57.1	○		○				
250	"	79.2	○		○	○		125	4,000	47.6	○		○	○				
300	"	95.2	○					125	5,000	59.5	○							

SUS304フラットバー 5


SUS304 FB HOT/ COLD/HL/#400研磨



寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間
12	125	6,000	71.4	○					16	150	6,000	114.0	○					
	150	4,000	57.2	○		○	○			200	4,000	102.0	○		○	○		
	150	5,000	71.5	○						250	"	127.0	○		○	○		
	150	6,000	85.8	○						300	"	152.0	○		○			
	200	4,000	76.0	○		○	○			25	"	15.1	○		○	○	○	
	250	"	95.2	○		○	○			30	"	18.1	○					
	300	"	114.0	○		○				32	"	19.3	○		○	○	○	
16	19	"	9.64			○	○		19	35	"	21.1	○					
	20	"	10.2	○		○	○	○		38	"	22.9	○		○	○	○	
	25	"	12.7	○		○	○	○		40	"	24.1	○					
	30	"	15.2	○						45	"	27.1	○					
	32	"	16.2	○		○	○	○		50	"	30.1	○		○	○	○	
	35	"	17.8	○						50	5,000	37.6	○					
	38	"	19.3	○		○	○	○		50	6,000	45.2	○					
	40	"	20.3	○		○	○	○		55	4,000	33.1	○					
	45	"	22.8	○						65	"	39.2	○		○	○		
	50	"	25.4	○		○	○	○		65	5,000	48.9	○					
	50	5,000	31.7	○						65	6,000	58.7	○					
	50	6,000	38.0	○		○				75	4,000	45.2	○		○	○		
	65	4,000	33.0	○		○	○			90	"	54.4	○					
	65	5,000	41.2	○						100	"	60.4	○		○	○		
	65	6,000	49.5	○		○				100	5,000	75.5	○					
	75	4,000	38.1	○		○	○			100	6,000	90.6	○					
	75	5,000	47.6	○						125	4,000	75.2	○		○	○		
	75	6,000	57.1	○		○				150	"	90.4	○		○	○		
	90	4,000	45.6	○						200	"	120.0	○		○	○		
	100	"	50.8	○		○	○			250	"	151.0	○		○	○		
	100	5,000	63.5	○						300	"	181.0	○		○			
	100	6,000	76.2	○		○				20	70	"	44.4	○				
	125	4,000	63.6	○		○	○				25	"	17.4	○				
125	5,000	79.5	○					30	"		20.9	○						
125	6,000	95.4	○					22	32		"	22.3	○		○			
150	4,000	76.0	○		○	○			35		"	24.4	○					
150	5,000	95.0	○						38		"	26.5	○		○			

SUS304フラットバー 6

SUS304 FB HOT/ COLD/HL/#400研磨



寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ			
22	40	4,000	27.9	○					30	250	4,000	238.0	○				
	45	"	31.4	○						300	"	286.0	○				
	50	"	34.9	○		○			35	50	"	55.60	○		○		
	65	"	45.2	○		○				65	"	72.00	○		○		
	75	"	52.4	○		○				75	"	83.20	○		○		
	90	"	62.8	○						100	"	111.0	○		○		
	100	"	69.6	○		○				125	"	139.0	○				
	125	"	87.2	○						150	"	166.0	○				
	150	"	105.0	○					40	50	"	63.60	○				
	200	"	140.0	○						65	"	82.40	○				
	250	"	174.0	○						75	"	95.20	○				
	300	"	209.0	○						100	"	127.0	○				
25	32	"	25.4	○		○				125	"	158.0	○				
	38	"	30.1	○		○				150	"	190.0	○				
	40	"	31.7	○					50	65	"	103.0	○				
	45	"	35.7	○				75		"	119.0	○					
	50	"	39.6	○		○				100	"	158.0	○				
	60	"	47.6	○						125	"	198.0	○				
	65	"	51.6	○		○				150	"	238.0	○				
	75	"	59.6	○		○				60	75	"	143.0	○			
	100	"	79.2	○		○			100		"	190.0	○				
	125	"	99.2	○		○			125		"	238.0	○				
	150	"	119.0	○		○			150		"	286.0	○				
	200	"	158.0	○		○			65		75	"	155.0	○			
250	"	198.0	○					70	100		"	222.0	○				
300	"	238.0	○						125	"	278.0	○					
30	50	"	47.6	○		○				150	"	333.0	○				
	55	"	52.4	○		○			80	100	"	254.0	○				
	65	"	62.0	○		○				125	"	317.0	○				
	75	"	71.2	○		○				150	"	381.0	○				
	100	"	95.2	○		○			90	125	"	357.0	○				
	125	"	119.0	○						150	"	428.0	○				
	150	"	143.0	○					100	125	"	396.0	○				
	200	"	190.0	○						150	"	476.0	○				