

銅板(CUP)

C1220P リン脱酸銅(DCuP) C1100P タフピッチ銅(TCuP) C1020P 無酸素銅(OFCuP)

● 在庫品 1枚の質量(kg/枚)

板厚 mm	品 種	寸 法 mm					
		365 × 1200	365 × 1212	455 × 1212	606 × 1212	1000 × 2000	1250 × 2500
0.1	タフピッチ	● 0.39					
0.15	"	● 0.59					
0.2	リン脱酸		● 0.80				
0.25	"		● 1.00				
0.3	"		● 1.20	● 1.49			
0.35	"		● 1.39	● 1.74	● 2.29		
0.4	"		● 1.59	● 1.99	● 2.62	● 7.2	
0.5	"		● 1.99	● 2.48		● 9.0	
0.6	無酸素 リン脱酸	● 2.37				● 10.8	
0.7	"	● 2.76					
0.8	"	● 3.15				● 14.4	
1.0	"	● 3.94				● 18.0	28.1
1.2	"	● 4.73				● 21.6	33.8
1.5	"	● 5.91				● 27.0	42.2
2.0	"	● 7.88				● 36.0	56.3
2.5	無酸素 タフピッチ	● 9.86				● 45.0	
3.0	"	● 11.8				● 54.0	84.4
4.0	"	● 15.8				● 72.0	112.5
5.0	"	● 19.7				● 90.0	140.5
6.0	"	● 23.7				● 108.0	168.8
7.0	タフピッチ						
8.0	"	● 31.5				● 144.0	
10.0	"	● 39.4				● 180.0	
12.0	"	● 47.3				● 216.0	
15.0	"	● 59.1				● 270.0	
20.0	"	● 78.8				● 360.0	
25.0	"	● 98.6				● 450.0	
30.0	"	● 118.3					
40.0	"	● 157.7					
50.0	"	● 197.1					

1250x2500はすべてタフピッチとなります。表記の質量はテーブル計算です。実際の商品は現物の実質量となります。

銅 条 (DCUR)

C1220R リン脱酸銅

● 在庫品

寸 法 mm		小コイル		大コイル	長さ1尺の 質量 (Kg/尺)	長さ1mの 質量 (KG/m)
幅	板厚	長さ m	制定質量 kg			
182	0.30		●		0.149	0.491
	0.35		●		0.174	0.573
	0.40		●		0.199	0.655
227	0.30		●		0.186	0.613
	0.35		●		0.217	0.715
	0.40		●		0.248	0.817
303	0.30	60	● 48.6	●	0.248	0.817
	0.35	50	● 47.3	●	0.289	0.954
	0.40	45	● 48.6	●	0.331	1.091
305	0.30		●	●	0.250	0.823
	0.35		●	●	0.291	0.960
	0.40		●	●	0.332	1.098
365	0.30	50	● 48.8		0.299	0.986
	0.35	40	● 45.6	●	0.348	1.150
	0.40	35	● 45.6	●	0.398	1.314
	0.50		●		0.498	1.643
455	0.25		●		0.310	1.024
	0.30	40	● 48.7	●	0.372	1.229
	0.35	35	● 49.7	●	0.434	1.433
	0.40	30	● 48.8	●	0.496	1.638
	0.50		●	●	0.620	2.048
500	0.30		●		0.409	1.350
	0.35		●		0.477	1.575
	0.40		●		0.545	1.800
606	0.30	30	● 48.7		0.496	1.636
	0.35	25	● 47.4	●	0.578	1.909
	0.40	20	● 43.4	●	0.661	2.182
	0.50		●	●	0.826	2.727
1000	☀ 0.30	20	●	●	0.818	2.700
	☀ 0.35	20	●	●	0.954	3.150
	☀ 0.40	20	●	●	1.091	3.600
	☀ 0.50	15	●	●	1.364	4.500

制定質量以外の商品は実質量となります。

☀は輸入材でJIS規格相当品となります

銅線・黄銅線 (CuW)

C1100W 銅線 C2700W黄銅線


● 在庫品

線径 mm	近似線番	軟銅線	硬銅線	黄銅線 1/4H	1000mの質量 kg		10kgの長さ m	
					銅線	黄銅線	銅線	黄銅線
8.0	0				452.6	427.0	22.1	23.4
7.0	2				346.2	327.0	28.9	30.6
6.0	4				254.3	240.2	39.3	41.6
5.0	6				176.6	166.8	56.6	59.9
4.5	7				143.1	135.1	69.9	74.0
4.0	8				113.0	106.8	88.5	93.7
3.2	10				72.34	68.32	138	146
3.0	11				63.58	60.05	157	167
2.6	12				47.75	45.10	209	222
2.3	13				37.37	35.29	268	283
2.0	14	●			28.26	26.69	354	375
1.8	15				22.89	21.61	437	463
1.6	16	●			18.08	17.08	553	585
1.4	17	●			13.84	13.07	723	765
1.2	18	●			10.17	9.60	983	1,042
1.0	19	●			7.06	6.67	1,416	1,499
0.9	20	●			5.72	5.40	1,748	1,852
0.8	21				4.52	4.27	2,212	2,342
0.7	22				3.46	3.26	2,890	3,067
0.6	23				2.54	2.40	3,937	4,167
0.55	24				2.14	2.02	4,673	4,951
0.5	25				1.76	1.66	5,682	6,024
0.45	26				1.43	1.35	6,993	7,407
0.4	27				1.13	1.07	8,850	9,346
0.35	28				0.87	0.82	11,494	12,195
0.3	30				0.64	0.60	15,625	16,667
0.25	31				0.44	0.42	22,727	23,810
0.2	33				0.28	0.27	35,714	37,037
0.1	36				0.07	0.07	142,857	142,857

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。

銅 管 (DCuT) 1

C1220T



切断品も対応 (別途ご相談)


調質: H・1/2H(表記なしはH)

寸 法 mm			1本の 質量 (kg/本)	寸 法 mm			1本の 質量 (kg/本)	寸 法 mm			1本の 質量 (kg/本)		
外径 D	肉厚 t	定尺長さ		外径 D	肉厚 t	定尺長さ		外径 D	肉厚 t	定尺長さ			
1.6	0.3	2,000	0.02	8.0	1.2	5,000	1.14	12.7	3.0	5,000	4.07		
2.0	0.4	"			1.5	"			1.37	1.0		"	1.82
2.5	0.4	"			2.0	"			1.68	1.2		"	2.15
3.0	0.5	2,500	0.09	9.0	1.0	"	1.12	14.0	1.5	"	2.63		
	0.8	5,000			1.5	"			1.58	2.0		"	3.36
3.2	0.5	2,500	0.10	9.5	0.6	"	0.75		15.0	3.0		"	4.62
3.5	0.5	"			0.8	"		0.97		1.0	"	1.96	
4.0	0.5	4,000	1.0		"	1.19		1.2		"	2.32		
	0.8	5,000	1.2	"	1.39	1.5	"	2.84					
	1.0	"	1.5	"	1.68	1.8	"	3.33					
4.5	0.5	2,500	0.14	10.0	2.0	"	2.10	15.9	2.0	"	3.64		
4.8	0.8	5,000			0.5	"			0.67	3.0		"	5.04
5.0	0.5	"	0.8		"	1.03			15.9	0.8		"	1.69
	0.8	"	1.0	"	1.26	1.0	"	2.09					
	1.0	"	1.2	"	1.48	1.2	"	2.47					
6.0	0.5	"	0.39	11.0	1.5	"	1.79	16.0	1.5	"	3.02		
	0.8	"			2.0	"			2.24	2.0		"	3.89
	1.0	"	1.0		"	1.40			3.0	"		5.42	
	1.2	"	1.5	"	2.00	2.0	"		3.92				
	1.5	"	2.0	"	2.52	2.5	"		4.73				
	2.0	"	0.8	"	1.25	4.0	"		6.72				
6.35	0.8	"	0.62	12.0	1.0	"	1.54	17.0	2.0	"	4.20		
	1.0	"			1.2	"			1.81	1.0		"	2.38
	1.2	"	1.5		"	2.21			1.2	"		2.82	
	1.5	"	2.0		"	2.80			1.5	"		3.47	
	2.0	"	3.0		"	3.78			2.0	"		4.48	
7.0	1.0	"	0.84	12.7	0.8	"	1.33	18.0	3.0	"	6.30		
	1.5	"			1.0	"			1.64	1.5		"	3.68
8.0	0.5	"	0.53		1.2	"			1.93	19.0		2.0	"
	0.8	"		1.5	"	2.35	3.0	"			6.72		
	1.0	"		2.0	"	3.00	4.0	"			8.40		

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

銅 管 (DCuT) 2

C1220T



切断品も対応 (別途ご相談)


調質: H・1/2H (表記なしはH)

寸 法 mm			1本の 質量 (kg/本)	寸 法 mm			1本の 質量 (kg/本)	寸 法 mm			1本の 質量 (kg/本)	
外径 D	肉厚 t	定尺長さ		外径 D	肉厚 t	定尺長さ		外径 D	肉厚 t	定尺長さ		
19.05	0.8	5,000	2.05	25.0	5.0	5,000	14.00	31.8	2.5	5,000	10.26	
	1.0	"	2.53		0.8	"	2.76		3.0	"	12.10	
	1.2	"	3.00		1.0	"	3.42		4.0	"	15.57	
20.0	1.0	"	2.66		1.2	"	4.07		5.0	"	18.76	
	1.2	"	3.16		25.4	1.5	"	5.02	34.0	2.0	"	8.96
	1.5	"	3.89			2.0	"	6.55		3.0	"	13.02
	1.8	"	4.59			2.5	"	8.02	35.0	1.5	"	7.04
	2.0	"	5.04			3.0	"	9.41		2.0	"	9.24
	2.5	"	6.13			5.0	"	14.28		2.5	"	11.38
	3.0	"	7.14	27.0	3.0	"	10.08	3.0		"	13.44	
	4.0	"	8.96		28.0	1.0	"	3.78		4.0	"	17.36
5.0	"	10.50	1.5			"	5.57	5.0		"	21.00	
22.0	1.0	"	2.94	2.0		"	7.28	38.0	1.0	"	5.18	
	1.5	"	4.31	3.0	"	10.50	1.2		"	6.18		
	2.0	"	5.60	28.6	1.0	"	3.86		1.5	"	7.67	
	2.5	"	6.83		1.2	"	4.60		2.0	"	10.08	
	3.0	"	7.98		1.5	"	5.69		2.5	"	12.43	
	3.5	"	9.07		2.0	"	7.45		3.0	"	14.70	
	4.0	"	10.08	3.0	"	10.75	4.0		"	19.04		
	5.0	"	11.90	30.0	1.0	"	4.06		5.0	"	23.10	
22.2	0.8	"	2.40		1.5	"	5.99	40.0	1.5	"	8.09	
	1.0	"	2.97		2.0	"	7.84		2.0	"	10.64	
24.0	2.0	"	6.16	2.5	"	9.63	2.5		"	13.13		
	25.0	1.0	"	3.36	3.0	"	11.34		3.0	"	15.54	
1.2		"	4.00	4.0	"	14.56	4.0		"	20.16		
1.5		"	4.94	5.0	"	17.50	5.0	"	24.50			
1.8		"	5.85	31.8	0.8	"	3.47	41.3	1.2	"	6.74	
2.0		"	6.44		1.0	"	4.31		1.5	"	8.36	
2.5		"	7.88		1.2	"	5.14		2.0	"	11.00	
3.0		"	9.24		1.5	"	6.36		3.0	"	16.09	
4.0	"	11.76	2.0		"	8.34	42.7	3.0	"	16.67		

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

銅 管 (DCuT) 3

C1220T



切断品も対応(別途ご相談)


調質:H・1/2H(表記なしはH)

寸 法 mm			1本の 質量 (kg/本)	寸 法 mm			1本の 質量 (kg/本)	寸 法 mm			1本の 質量 (kg/本)
外径 D	肉厚t	定尺長さ		外径 D	肉厚t	定尺長さ		外径 D	肉厚t	定尺長さ	
44.5	1.0	5,000	6.09	63.5	2.5	5,000	21.35				
	1.2	"	7.27		3.0	"	25.41				
	1.5	"	9.03		4.0	"	33.32				
	2.0	"	11.90		5.0	"	40.95				
	3.0	"	17.43	65.0	3.0	"	26.04				
45.0	2.0	"	12.04	66.68	1.5	"	13.69				
	2.5	"	14.88	66.80	2.0	"	18.14				
	5.0	"	28.00	70.0	2.0	"	19.04				
48.0	3.0	"	18.90		3.0	"	28.14				
48.6	3.0	"	19.15		5.0	"	45.50				
50.0	1.5	"	10.19	76.2	1.5	"	15.69				
	2.0	"	13.44		2.0	"	20.78				
	3.0	"	19.74		3.0	"	30.74				
	5.0	"	31.50		4.0	"	40.43				
50.8	1.2	"	8.33	80.0	5.0	"	49.84				
	1.5	"	10.35		3.0	"	32.34				
	2.0	"	13.66	82.5	5.0	"	52.50				
	2.5	"	16.91		3.0	"	33.39				
	3.0	"	20.08	88.9	5.0	"	54.25				
	4.0	"	26.21		2.0	"	24.33				
	5.0	"	32.06		3.0	"	36.08				
55.0	2.0	"	14.84	101.6	5.0	"	58.73				
	2.5	"	18.38		2.0	"	27.89				
	3.0	"	21.84	110.0	3.0	"	41.41				
	5.0	"	35.00		5.0	"	67.62				
60.0	1.5	"	12.29	114.3	5.0	"	73.50				
	2.0	"	16.24	120.0	3.0	"	46.75				
	3.0	"	23.94	130.0	5.0	"	80.50				
	5.0	"	38.50	140.0	5.0	"	87.50				
63.5	1.5	"	13.02	150.0	5.0	"	94.50				
	2.0	"	17.22				101.50				

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

軟銅管 (DCuT-Oコイル) 1

C1220T-O




調質: O/一部OL

寸法 (mm x mm)		定尺長さ m	寸法 (mm x mm)		定尺長さ m	寸法 (mm x mm)		定尺長さ m	
外径 D	肉厚 t		外径 D	肉厚 t		外径 D	肉厚 t		
3.0	0.5	10	6.35	0.8	10	10.0	1.0	5	
	0.5	100		0.8	20		1.0	10	
3.2	0.5	10		0.8	50		1.0	20	
4.0	0.5	10		1.0	10		1.0	30	
	0.5	20		1.0	20		1.0	50	
	0.8	10		1.0	50		1.0	100	
	0.8	20		8.0	0.8		10	1.2	10
	1.0	10			0.8		20	1.2	20
1.0	20	1.0			5		1.2	30	
4.8	0.8	10			1.0		10	1.2	100
	0.8	20	1.0		20	1.5	10		
5.0	0.8	10	1.0		30	1.5	20		
	0.8	20	1.0		50	1.5	30		
	1.0	10	1.0		100	1.5	100		
	1.0	20	1.2		10	2.0	10		
6.0	0.6	10	1.2		20	2.0	20		
	0.8	10	1.5	10	2.0	30			
	0.8	20	1.5	20	12.0	0.8	10		
	0.8	100	2.0	10		0.8	20		
	1.0	5	2.0	20		1.0	5		
	1.0	10	9.5	0.8		10	1.0	10	
	1.0	20		0.8		20	1.0	20	
	1.0	30		0.8		50	1.0	50	
	1.0	50		1.0		10	1.0	100	
	1.0	100		1.0		20	1.2	10	
	1.2	10		1.0		100	1.2	20	
	1.2	20		1.2		10	1.2	30	
	1.2	30		1.2	20	1.5	10		
	1.5	10		10.0	0.8	10	1.5	20	
	1.5	20			0.8	20	1.5	30	

表示している規格は標準在庫品です。

軟銅管 (DCuT-Oコイル) 2

C1220T-O



調質: O/一部OL

寸法 (mm x mm)		定尺長さ m	寸法 (mm x mm)		定尺長さ m	寸法 (mm x mm)		定尺長さ m
外径 D	肉厚 t		外径 D	肉厚 t		外径 D	肉厚 t	
12.0	2.0	20	15.9	1.20	20			
	2.0	30		1.50	10			
12.7	0.8	10		16.0	1.50	20		
	0.8	20	2.00		20			
	1.0	10	19.0	0.80	10			
	1.00	20		0.80	20			
	1.00	50		1.00	10			
	1.20	10		1.00	20			
	1.20	20		1.20	10			
	1.50	10		1.20	20			
	1.50	20		1.50	10			
	1.50	30		1.50	20			
14.0	1.00	10	22.2	1.00	10			
	1.00	20		1.00	20			
15.0	1.00	5						
	1.00	10						
	1.00	20						
	1.20	10						
	1.20	20						
	1.50	10						
	1.50	20						
	2.00	10						
	2.00	20						
	2.00	30						
15.9	0.80	10						
	0.80	20						
	1.00	10						
	1.00	20						
	1.00	50						
	1.20	10						

表示している規格は標準在庫品です。


銅管継手

● 在庫品

呼径	品名 外径	ソケット	レジューサー	ティーズ	90° エルボ	45° エルボ	オスアダ プター-A	メスアダ プター-A	ユニオン	キャップ	水栓 エルボ	絶縁 ユニオン
1/8	6.35	●		●								
1/4	9.53	●		●								
異型		●	●	●								
3/8	12.70	●		●	●	●	●	●	●	●		
異型		●	●	●								
1/2	15.88	●		●	●	●	●	●	●	●	●	●
異型		●	●	●	●		●	●				
5/8	19.05	●		●	●	●			●	●		
異型		●	●	●								
3/4	22.20	●		●	●	●	●	●	●	●	●	●
異型		●	●	●	●		●	●			●	
7/8	25.40	●		●	●	●				●		
異型		●	●	●								
1"	28.58	●		●	●	●	●	●	●	●	●	●
異型		●	●	●	●							
1 1/8	31.80	●		●	●	●				●		
異型		●	●	●								
1 1/4	34.93	●		●	●	●	●	●	●	●		●
異型		●	●	●	●							
1 3/8	38.10	●	●	●	●	●				●		
異型		●	●	●								
1 1/2	41.28	●		●	●	●	●	●	●	●		●
異型		●	●	●								
1 7/8	50.80	●		●	●	●				●		
異型		●	●	●								
2"	53.98	●		●	●	●	●	●	●	●		●
異型		●	●	●								
2 1/2	66.68	●	●	●	●	●	●	●	●	●		●
3"	79.38	●	●	●	●	●	●		●	●		
3 1/2	92.08											
4"	104.78	●	●	●	●	●	●		●	●		

銅丸棒 (TCuB)

C1100B




切断品も対応(別途ご相談)

寸法 mm		1本の質量 (kg/本)	寸法 mm		1本の質量 (kg/本)
直径 D	定尺長さ		直径 D	定尺長さ	
3	2,000	0.13	28	4,000	21.9
4	"	0.22	30	"	25.2
5	"	0.35	32	"	28.7
6	"	0.50	35	"	34.3
7	"	0.68	36	"	36.3
8	"	0.90	38	"	40.4
9	"	1.13	40	"	44.8
10	"	1.40	42	"	49.4
5	4,000	0.70	45	"	56.7
6	"	1.00	48	"	64.5
7	"	1.37	50	"	70.0
8	"	1.80	55	"	84.7
9	"	2.27	60	"	100.8
10	"	2.80	65	"	118.3
11	"	3.40	70	"	137.2
12	"	4.00	75	"	157.5
13	"	4.70	80	"	179.2
14	"	5.50	85	"	202.3
15	"	6.30	90	"	226.8
16	"	7.20	95	"	252.7
17	"	8.10	100	"	280.0
18	"	9.10	105	"	308.7
19	"	10.1	110	"	338.8
20	"	11.2	120	"	403.2
21	"	12.3	130	"	473.2
22	"	13.6	150	乱尺	(158kg/m)
23	"	14.8	180	乱尺	(227kg/m)
24	"	16.1			
25	"	17.5			
26	"	18.9			

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

銅 帯 (CuBB)1

C1100BB-1/2H



切断品も対応(別途ご相談)

寸 法 mm			1本の 質量 (kg/本)	寸 法 mm			1本の 質量 (kg/本)	寸 法 mm			1本の 質量 (kg/本)
厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ	
2	10	5,000	0.9	4	50	5,000	9.0	6	60	5,000	16.2
	12	"	1.1		60	"	10.8		65	"	17.6
	15	"	1.4	5	12	"	2.7		75	"	20.3
	20	"	1.8		15	"	3.4		80	"	21.6
	25	"	2.3		18	"	4.1		100	"	27.0
	30	"	2.7		20	"	4.5		125	"	33.8
3	10	"	1.4		22	"	5.0	150	"	40.5	
	12	"	1.6		25	"	5.6	200	"	54.0	
	14	"	1.9	30	"	6.8	8	15	"	5.4	
	15	"	2.0	32	"	7.2		20	"	7.2	
	16	"	2.2	35	"	7.9		25	"	9.0	
	18	"	2.4	40	"	9.0		28	"	10.1	
	20	"	2.7	45	"	10.1		30	"	10.8	
	25	"	3.4	50	"	11.3		35	"	12.6	
	30	"	4.1	60	"	13.5		40	"	14.4	
	32	"	4.3	75	"	16.9		50	"	18.0	
	35	"	4.7	100	"	22.5		60	"	21.6	
	40	"	5.4	125	"	28.1		65	"	23.4	
	50	"	6.8	6	12	"		3.2	75	"	27.0
	75	"	10.1		15	"		4.1	80	"	28.8
4	10	"	1.8		18	"		4.9	100	"	36.0
	12	"	2.2		20	"		5.4	125	"	45.0
	15	"	2.7		25	"	6.8	150	"	54.0	
	18	"	3.2		30	"	8.1	200	"	72.0	
	20	"	3.6	32	"	8.6	10	20	"	9.0	
	25	"	4.5	35	"	9.5		25	"	11.3	
	30	"	5.4	38	"	10.3		30	"	13.5	
	35	"	6.3	40	"	10.8		35	"	15.8	
	40	"	7.2	50	"	13.5		40	"	18.0	

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

銅 帯 (CuBB)2

C1100BB-1/2H



切断品も対応 (別途ご相談)

寸 法 mm			1本の 質量 (kg/本)	寸 法 mm			1本の 質量 (kg/本)	寸 法 mm			1本の 質量 (kg/本)
厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ	
10	50	5,000	22.5	20	30	5,000	27.0				
	60	"	27.0		40	"	36.0				
	75	"	33.8		50	"	45.0				
	80	"	36.0		75	"	67.5				
	100	"	45.0		100	"	90.0				
	125	"	56.3		125	"	112.5				
	150	"	67.5		150	"	135.0				
	200	"	90.0		200	"	180.0				
12	20	"	10.8	25	250	"	225.0				
	30	"	16.2		30	"	33.8				
	40	"	21.6		40	"	45.0				
	50	"	27.0		50	"	56.3				
	60	"	32.4		75	"	84.4				
	75	"	40.5		80	"	90.0				
	100	"	54.0		100	"	112.5				
	125	"	67.5		30	100	4,000	108.0			
	150	"	81.0								
	200	"	108.0								
15	20	"	13.5								
	25	"	16.9								
	30	"	20.3								
	40	"	27.0								
	50	"	33.8								
	75	"	50.7								
	100	"	67.5								
	125	"	84.4								
	150	"	101.3								
	200	"	135.0								
	250	"	168.8								

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。