

# 黄銅板 (BsP)

C2801P-1/4H・F

● 在庫品  
1枚の質量(kg/枚)

板厚 mm	寸 法 mm			板厚 mm	寸 法 mm		
	365x1200	1000x2000	1250x2500		365x1200	1000x2000	1250x2500
0.1	● 0.38 2種			12.0	● 45.0	● 204.0	
0.15	● 0.56 2種			15.0	● 56.3	● 255.0	
0.2	● 0.75			20.0	● 75.0	● 340.0	
0.25	● 0.9			25.0	● 93.8		
0.3	● 1.1			30.0	● 112.5		
0.4	● 1.5			35.0	● 131.3 F		
0.5	● 1.9			40.0	● 150.0 F		
0.6	● 2.3	● 10.2		50.0	● 187.5 F		
0.7	● 2.6						
0.8	● 3.0	● 13.6					
1.0	● 3.8	● 17.0	● 26.6				
1.2	● 4.5	● 20.4	● 31.9				
1.4	● 5.3						
1.5	● 5.6	● 25.5	● 39.8				
1.6	● 6.0	● 27.2					
1.8	● 6.8						
2.0	● 7.5	● 34.0	● 53.1				
2.3	● 8.6						
2.5	● 9.4	● 42.5					
2.6	● 9.8						
3.0	● 11.2	● 51.0	● 79.7				
3.2	● 12.0	● 54.4					
3.5	● 13.1						
4.0	● 15.0	● 68.0	● 106.3				
4.5	● 16.9						
5.0	● 18.8	● 85.0	● 132.8				
6.0	● 22.5	● 102.0					
8.0	● 30.0	● 136.0					
10.0	● 37.5	● 170.0					

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。 F: 製造したままのもの

# 銅線・黄銅線(CuW)

C1100W 銅線 C2700W黄銅線


● 在庫品

線径 mm	近似線番	軟銅線	硬銅線	黄銅線 1/4H	1000mの質量 kg		10kgの長さ m	
					銅線	黄銅線	銅線	黄銅線
8.0	0				452.6	427.0	22.1	23.4
7.0	2				346.2	327.0	28.9	30.6
6.0	4				254.3	240.2	39.3	41.6
5.0	6				176.6	166.8	56.6	59.9
4.5	7				143.1	135.1	69.9	74.0
4.0	8				113.0	106.8	88.5	93.7
3.2	10				72.34	68.32	138	146
3.0	11				63.58	60.05	157	167
2.6	12				47.75	45.10	209	222
2.3	13				37.37	35.29	268	283
2.0	14	●			28.26	26.69	354	375
1.8	15				22.89	21.61	437	463
1.6	16	●			18.08	17.08	553	585
1.4	17	●			13.84	13.07	723	765
1.2	18	●			10.17	9.60	983	1,042
1.0	19	●			7.06	6.67	1,416	1,499
0.9	20	●			5.72	5.40	1,748	1,852
0.8	21				4.52	4.27	2,212	2,342
0.7	22				3.46	3.26	2,890	3,067
0.6	23				2.54	2.40	3,937	4,167
0.55	24				2.14	2.02	4,673	4,951
0.5	25				1.76	1.66	5,682	6,024
0.45	26				1.43	1.35	6,993	7,407
0.4	27				1.13	1.07	8,850	9,346
0.35	28				0.87	0.82	11,494	12,195
0.3	30				0.64	0.60	15,625	16,667
0.25	31				0.44	0.42	22,727	23,810
0.2	33				0.28	0.27	35,714	37,037
0.1	36				0.07	0.07	142,857	142,857

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。

# 黄銅管(BsT) 1

C2700T



切断品も対応(別途ご相談)


調質:H

寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)
外径 D	肉厚 t	定尺長さ		外径 D	肉厚 t	定尺長さ		外径 D	肉厚 t	定尺長さ	
1.6	0.3	2,000	0.02	9.0	0.8	5,000	0.88	13.0	1.0	5,000	1.61
2.0	0.35	"	0.03		1.0	"	1.07		2.0	"	2.95
2.5	0.4	"	0.05		1.5	"	1.51	14.0	0.8	"	1.42
3.0	0.5	2,500	0.08	9.53	0.5	"	0.61		1.0	"	1.74
3.2	0.5	"	0.09		0.8	"	0.94		1.5	"	2.51
3.5	0.5	"	0.10		1.0	"	1.14		2.0	"	3.22
4.0	0.5	"	0.12		1.2	"	1.34	3.0	"	4.42	
	0.8	"	0.17		1.5	"	1.61	15.0	1.0	"	1.88
1.0	"	0.20	10.0	0.5	"	0.64	1.2		"	2.22	
4.5	0.5	"		0.13	0.8	"	0.99		1.5	"	2.71
5.0	0.5	"		0.15	1.0	"	1.21	2.0	"	3.48	
	0.8	5,000		0.45	1.2	"	1.42	15.9	0.5	"	1.03
	1.0	"		0.54	1.5	"	1.71		0.8	"	1.62
5.5	0.5	2,500	0.17	2.0	"	2.14	1.0		"	2.00	
6.0	0.5	5,000	0.37	11.0	0.5	"	0.70		1.2	"	2.36
	0.8	"	0.56		0.8	"	1.09		1.5	"	2.89
	1.0	"	0.67		1.0	"	1.34	2.0	"	3.73	
	1.2	"	0.77		1.5	"	1.91	3.0	"	5.19	
	1.5	"	0.90		2.0	"	2.41	16.0	1.5	"	2.72
6.4	0.5	"	0.40	12.0	0.5	"	0.77		2.0	"	3.75
	0.8	"	0.60		0.8	"	1.20	17.0	2.0	"	4.02
	1.0	"	0.72		1.0	"	1.47	18.0	1.0	"	2.28
7.0	0.5	"	0.44		1.2	"	1.74		1.5	"	3.32
	1.0	"	0.80		1.5	"	2.11		2.0	"	4.29
8.0	0.5	"	0.50	2.0	"	2.68	3.0	"	6.03		
	0.8	"	0.77	12.7	0.5	"	0.82	19.0	0.5	"	1.24
	1.0	"	0.94		0.8	"	1.28		0.8	"	1.95
	1.2	"	1.09		1.0	"	1.57		1.0	"	2.41
	1.5	"	1.31		1.2	"	1.85		1.2	"	2.86
	2.0	"	1.61		1.5	"	2.25		1.5	"	3.52
9.0	0.5	"	0.57		2.0	"	2.87		2.0	"	4.56

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# 黄銅管(BsT)2

C2700T



切断品も対応(別途ご相談)


調質:H

寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)
外径 D	肉厚 t	定尺長さ		外径 D	肉厚 t	定尺長さ		外径 D	肉厚 t	定尺長さ	
19.0	3.0	5,000	6.43	27.0	1.0	5,000	3.49	32.0	2.0	5,000	8.04
20.0	1.0	"	2.55		3.5	"	11.20		34.0	1.5	"
	1.5	"	3.72	27.2	1.5	"	5.17	2.0		"	8.58
	2.0	"	4.82		3.0	"	9.73	3.0		"	12.46
	3.0	"	6.83	28.0	0.8	"	2.92	35.0	1.0	"	4.56
21.7	2.5	"	6.43		1.0	"	3.62		1.2	"	5.44
22.0	0.5	"	1.44		1.5	"	5.33		1.5	"	6.73
	0.8	"	2.27		2.0	"	6.97		2.0	"	8.84
	1.0	"	2.81		3.0	"	10.05		2.5	"	10.89
	1.2	"	3.34		4.0	"	12.86		3.0	"	12.86
	1.5	"	4.12		28.58	1.0	"		3.70	4.0	"
	2.0	"	5.36	1.5		"	5.44	5.0	"	20.10	
	3.0	"	7.64	2.0		"	7.12	36.0	1.5	"	6.93
4.0	"	9.65	3.0	"		10.28	3.0		"	13.27	
22.2	1.0	"	2.84	5.0	"	15.80	38.0	0.8	"	3.99	
24.0	2.0	"	5.90	30.0	1.0	"		3.89	1.0	"	4.96
25.0	1.0	"	3.22		1.5	"		5.73	1.2	"	5.92
	1.2	"	3.83		2.0	"		7.50	1.5	"	7.34
	1.5	"	4.73		2.5	"		9.22	2.0	"	9.65
	2.0	"	6.16		3.0	"		10.85	3.0	"	14.07
	2.5	"	7.54		4.0	"	13.94	5.0	"	22.11	
	3.0	"	8.84		5.0	"	16.75	40.0	1.0	"	5.23
25.4	0.5	"	1.67	31.8	0.8	"	3.32		1.5	"	7.74
	0.8	"	2.64		1.0	"	4.13		2.0	"	10.18
	1.0	"	3.27		1.2	"	4.92		3.0	"	14.87
	1.2	"	3.89		1.5	"	6.09		4.0	"	19.30
	1.5	"	4.80		2.0	"	7.99		5.0	"	23.45
	2.0	"	6.27		3.0	"	11.58		41.3	1.5	"
	2.5	"	7.67		4.0	"	14.90	3.0		"	15.40
	3.0	"	9.00		5.0	"	17.96	42.0	1.0	"	5.49
	5.0	"	13.67		32.0	1.5	"		6.13	2.0	"

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# 黄銅管(BsT)3

C2700T



切断品も対応(別途ご相談)


調質:H

寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)		
外径 D	肉厚 t	定尺長さ		外径 D	肉厚 t	定尺長さ		外径 D	肉厚 t	定尺長さ			
42.0	4.0	5,000	20.37	60.0	1.0	5,000	7.91	88.9	4.0	5,000	45.51		
42.7	1.5	"	8.28		1.5	"	11.76		5.0	"	56.21		
	2.0	"	10.91		2.0	"	15.54	95.0	3.0	"	36.98		
	3.0	"	15.96		3.0	"	22.91		5.0	"	60.30		
44.5	1.0	"	5.83		4.0	"	30.02	101.6	1.5	"	21.44		
	1.5	"	8.64		5.0	"	36.85		2.0	"	26.69		
	2.0	"	11.39		63.5	1.2	"		10.02	3.0	"	39.64	
	3.0	"	16.68			1.5	"		12.46	4.0	"	52.31	
	5.0	"	26.47			2.0	"		16.48	5.0	"	64.72	
45.0	5.0	"	26.80			3.0	"		24.32	6.0	"	76.86	
46.0	3.0	"	17.29			4.0	"		31.89	108.0	3.0	"	42.21
48.0	1.5	"	9.35			5.0	"		39.20	110.0	5.0	"	70.35
	5.0	"	28.81	65.0		3.0	"		24.92	114.3	3.0	"	44.74
48.6	1.5	"	9.47			5.0	"		40.20	5.0	"	73.23	
	2.0	"	12.49	70.0	2.0	"	18.22	120.0	3.0	"	47.03		
	3.0	"	18.33		3.0	"	26.93	5.0	"	77.05			
50.0	1.5	"	9.75	5.0	"	43.55	127.0	3.0	"	49.85			
	2.0	"	12.86	75.0	3.0	"		28.94	5.0	"	81.74		
	3.0	"	18.89		5.0	"	46.90	130.0	5.0	"	83.75		
	4.0	"	24.66		1.5	"	15.02	135.0	5.0	"	87.10		
	5.0	"	30.15	2.0	"	19.89	140.0	5.0	"	90.45			
50.8	1.0	"	6.67	76.2	3.0	"	29.43	150.0	3.0	"	59.09		
	1.2	"	7.98		4.0	"	38.70		5.0	"	97.15		
	1.5	"	9.91		5.0	"	47.70	152.4	5.0	"	98.76		
	2.0	"	13.08	80.0	3.0	"	30.95	160.0	5.0	"	103.85		
	3.0	"	19.22		5.0	"	50.25	165.0	5.0	"	107.20		
	4.0	"	25.08	82.5	3.0	"	31.96	180.0	5.0	"	117.25		
	5.0	"	30.69		5.0	"	51.93	200.0	5.0	"	130.65		
	55.0	3.0	"	20.90	88.9	1.5	"	17.57					
5.0		"	33.50	2.0		"	23.29						
57.0	3.0	"	21.71	3.0		"	34.54						

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# 黄銅四角管 (BsT四角管)

C2700T相当品



切断品も対応(別途ご相談)


調質:H

寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)
辺 A	肉厚 t	定尺長さ		辺 A	肉厚 t	定尺長さ	
6	1.0	4,000	0.7	32	1.2	5,000	6.2
8	1.0	"	1.0		1.5	"	7.7
9	1.0	5,000	1.4	35	1.5	"	9.0
	1.2	"	1.6	38	1.5	"	9.8
9.5	1.0	"	1.5	40	1.5	"	10.0
	1.2	"	1.7	50	1.5	"	12.9
12	1.0	"	1.8	60	1.5	"	15.4
	1.5	"	2.7	75	2.0	"	24.6
12.7	1.0	"	2.0	100	3.0	"	49.2
	1.2	"	2.4				
	1.5	"	3.0				
15	1.5	"	3.4				
15.9	1.0	"	2.6				
	1.2	"	3.0				
	1.5	"	3.8				
19	1.0	"	2.8				
	1.5	"	4.5				
20	1.5	"	4.7				
22	1.0	"	3.6				
	1.2	"	4.8				
	1.5	"	5.6				
25	1.5	"	6.0				
25.4	1.0	"	4.2				
	1.2	"	4.6				
	1.5	"	6.2				
28	1.2	"	5.3				
	1.5	"	6.4				
30	1.2	"	5.9				
	1.5	"	7.3				

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# 黄銅平角管 (BsT平角管)

G2700T相当品



切断品も対応(別途ご相談)


調質:H

寸 法 mm				1本の 質量 (kg/本)	寸 法 mm				1本の 質量 (kg/本)
辺 A	辺 B	肉厚 t	定尺長さ		辺 A	辺 B	肉厚 t	定尺長さ	
15	10	1.0	5,000	2.0	20	12	0.7	4,000	1.4
	10	1.2	"	2.4	24	15	0.8	"	2.0
20	10	1.2	"	2.8	30	20	0.9	"	3.0
22	10	1.2	"	3.1					
	12	1.2	"	3.3					
24	15	1.2	"	3.8					
25	12	1.2	"	3.6					
	12	1.5	"	4.4					
30	10	1.2	"	3.8					
	15	1.5	"	5.4					
	20	1.2	"	4.9					
	20	1.5	"	6.1					
40	16	1.0	"	4.6					
	16	1.5	"	6.8					
	20	1.5	"	7.4					
	25	1.5	"	8.6					
50	20	1.5	"	8.7					
	25	1.5	"	9.2					
	30	1.5	"	10.0					
60	30	1.5	"	12.0					
80	40	2.0	"	20.6					
100	50	2.0	"	25.9					

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# 黄銅丸棒 (BsBM)

C3604B 快削黄銅丸棒




切断品も対応(別途ご相談)

寸法 mm		1本の質量 (kg/本)	寸法 mm		1本の質量 (kg/本)	寸法 mm		1本の質量 (kg/本)
直径 D	定尺長さ		直径 D	定尺長さ		直径 D	定尺長さ	
5	2,000	0.3	34	4,000	30.6	115	乱尺	
6	"	0.5	35	"	32.4	120	乱尺	
8	"	0.9	36	"	34.3	130	乱尺	
9	"	1.1	38	"	38.3	140	乱尺	
10	"	1.3	40	"	42.4	150	乱尺	
10	4,000	2.6	41	"	45.0	160	乱尺	
11	"	3.2	42	"	46.7			
12	"	3.8	44	"	51.2			
13	"	4.5	45	"	53.6			
14	"	5.2	46	"	56.0			
15	"	6.0	48	"	61.0			
16	"	6.8	50	"	66.2			
17	"	7.7	51	"	69.7			
18	"	8.6	52	"	72.4			
19	"	9.6	54	"	78.1			
20	"	10.6	55	"	80.1			
21	"	11.7	58	"	90.0			
22	"	12.8	60	"	96.0			
23	"	14.0	62	"	103.0			
24	"	15.3	65	"	113.0			
25	"	16.6	70	"	131.0			
26	"	17.9	75	"	151.0			
27	"	19.3	80	"	171.0			
28	"	20.8	85	"	193.0			
29	"	22.3	90	乱尺				
30	"	23.8	95	乱尺				
31	"	25.5	100	乱尺				
32	"	27.1	105	乱尺				
33	"	29.0	110	乱尺				

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# 黄銅六角棒 (BsBM)

C3604B 快削黄銅六角棒




寸 法 mm		1本の質量 (kg/本)	寸 法 mm		1本の質量 (kg/本)
対辺 A	定尺長さ		対辺 A	定尺長さ	
10	4,000	2.9	50	4,000	73.0
12	"	4.2	54	"	86.0
13	"	5.0	55	"	89.0
14	"	5.8	58	"	99.0
15	"	6.6	60	"	106.0
16	"	7.5	65	"	124.0
17	"	8.5	70	"	144.0
18	"	9.5			
19	"	10.6			
20	"	11.7			
21	"	12.9			
22	"	14.2			
23	"	15.5			
24	"	16.9			
25	"	18.3			
26	"	19.8			
27	"	21.3			
28	"	22.9			
29	"	24.6			
30	"	26.3			
32	"	30.0			
34	"	33.8			
35	"	35.8			
36	"	37.9			
38	"	42.2			
40	"	46.8			
41	"	49.5			
45	"	59.2			
46	"	61.9			

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# 黄銅四角棒 (BsBM)

C3604B 快削黄銅四角棒




切断品も対応(別途ご相談)

寸 法 mm		1本の質量 (kg/本)	寸 法 mm		1本の質量 (kg/本)
辺 A	定尺長さ		辺 A	定尺長さ	
10	4,000	3.4			
12	"	4.9			
13	"	5.7			
14	"	6.6			
15	"	7.6			
16	"	8.7			
17	"	9.8			
18	"	11.0			
19	"	12.2			
20	"	13.5			
22	"	16.4			
25	"	21.1			
26	"	22.7			
30	"	30.4			
32	"	34.6			
35	"	41.3			
38	"	49.1			
40	"	54.0			
45	"	68.3			
50	"	84.3			
55	"	102.0			
60	"	121.4			
65	"	143.7			
70	"	166.6			
75	3,500	167.3			
80	3,000	163.2			

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# 黄銅平角棒 (BsBM) 1

C3604B相当品



切断品も対応 (別途ご相談)

寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)
厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ	
3	6	4,000	0.61	4	25	4,000	3.40	5	45	4,000	7.65
	8	"	0.82		30	"	4.08		50	"	8.50
	9	"	0.92		32	"	4.35		60	"	10.20
	10	"	1.02		35	"	4.76	6	8	"	1.63
	12	"	1.22		40	"	5.44		9	"	1.84
	15	"	1.53		50	"	6.80		10	"	2.04
	16	"	1.63	4.5	6	"	0.92		12	"	2.45
	18	"	1.84		9	"	1.38		13	"	2.65
	19	"	1.94		10	"	1.53		14	"	2.86
	20	"	2.04		12	"	1.84		15	"	3.06
	22	"	2.24		15	"	2.30		16	"	3.26
	25	"	2.55		18	"	2.75		18	"	3.67
	30	"	3.06		20	"	3.06	19	"	3.88	
	32	"	3.26		25	"	3.83	20	"	4.08	
	35	"	3.57		30	"	4.59	22	"	4.49	
	38	"	3.88	35	"	5.36	25	"	5.10		
	40	"	4.08	38	"	5.81	30	"	6.12		
	45	"	4.59	50	"	7.65	32	"	6.53		
50	"	5.10	5	10	"	1.70	35	"	7.14		
4	6	"		0.82	12	"	2.04	38	"	7.75	
	7	"		0.95	15	"	2.55	40	"	8.16	
	8	"		1.09	16	"	2.72	45	"	9.18	
	9	"		1.22	19	"	3.23	50	"	10.20	
	10	"		1.36	20	"	3.40	60	"	12.24	
	12	"		1.63	25	"	4.25	65	"	13.26	
	15	"		2.04	30	"	5.10	75	"	15.30	
	16	"		2.18	32	"	5.44	100	"	20.40	
	18	"		2.45	35	"	5.95	7	12	"	2.86
	20	"	2.72	40	"	6.80	13		"	3.09	

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# 黄銅平角棒 (BsBM) 2

C3604B相当品




切断品も対応 (別途ご相談)

寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)	
厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ		
7	20	4,000	4.76	10	15	4,000	5.10	12	50	4,000	20.40	
8	10	"	2.72		16	"	5.44		60	"	24.48	
	12	"	3.26		18	"	6.12		80	"	32.64	
	15	"	4.08		20	"	6.80		100	"	40.80	
	16	"	4.35		22	"	7.48	13	25	"	11.05	
	18	"	4.90		25	"	8.50	14	20	"	9.52	
	20	"	5.44		30	"	10.20	15	20	"	10.20	
	22	"	5.98		35	"	11.90		22	"	11.22	
	25	"	6.80		40	"	13.60		25	"	12.75	
	30	"	8.16		45	"	15.30		30	"	15.30	
	35	"	9.52		50	"	17.00		35	"	17.85	
	38	"	10.34		55	"	18.70		40	"	20.40	
	40	"	10.88		60	"	20.40		45	"	22.95	
	50	"	13.60		65	"	22.10		50	"	25.50	
	60	"	16.32		75	"	25.50		55	"	28.05	
75	"	20.40	80		"	27.20	60		"	30.60		
100	"	27.20	100		"	34.00	65	"	33.15			
9	12	"	3.67		12	14	"	5.71	16	80	"	40.80
	15	"	4.59			15	"	6.12		100	"	51.00
	18	"	5.51	16		"	6.53	18		"	9.79	
	20	"	6.12	18		"	7.34	20	"	10.88		
	25	"	7.65	20		"	8.16	25	"	13.60		
	30	"	9.18	22		"	8.98	30	"	16.32		
	32	"	9.79	25		"	10.20	40	"	21.76		
	35	"	10.71	30		"	12.24	50	"	27.20		
	38	"	11.63	35		"	14.28	17	25	"	14.45	
	40	"	12.24	38		"	15.50	18	20	"	12.24	
	50	"	15.30	40		"	16.32	20	25	"	17.00	
10	12	"	4.08	45	"	18.36	30		"	20.40		

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# 黄銅平角棒 (BsBM) 3

C3604B相当品




切断品も対応(別途ご相談)

寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)
厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ	
20	35	4,000	23.80								
	40	"	27.20								
	45	"	30.60								
	50	"	34.00								
	55	"	37.40								
	60	"	40.80								
	65	"	44.20								
	75	"	51.00								
100	"	68.00									
22	40	"	29.92								
25	30	"	25.50								
	35	"	29.75								
	40	"	34.00								
	45	"	38.25								
	50	"	42.50								
	55	"	46.75								
	60	"	51.00								
75	"	63.75									
30	35	"	35.70								
	40	"	40.80								
	45	"	45.90								
	50	"	51.00								
	55	"	56.10								
	60	"	61.20								
	65	"	66.30								
75	"	76.50									
35	40	"	47.60								
	50	"	59.50								
	60	"	71.40								

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# 黄銅アンゲル (BsBM)

C3604相当品




寸 法 mm			1本の質量 (kg/本)
辺 A	厚さ t	定尺長さ	
9	3.0	4,000	1.53
9.5	1.2	"	0.73
12	3.0	"	2.14
15	1.2	"	1.21
	1.5	"	1.45
	2.0	"	1.90
	3.0	"	2.75
16	3.0	"	2.96
19	1.2	"	1.50
20	2.0	"	2.58
	3.0	"	3.77
25	2.0	"	3.26
	3.0	"	4.79
	5.0	"	7.70
30	2.0	"	3.94
	3.0	"	5.81
	4.0	"	7.60
	5.0	"	9.35
38	3.0	"	7.45
40	3.0	"	7.90
	4.0	"	10.34
50	3.0	"	9.90
	4.0	"	13.00
	5.0	"	16.15

表記の質量はテーブル計算です。実際の商品は現物の実重量となります。重量を表示している規格は標準在庫品です。

# カドミフリー黄銅棒 (BsBM)

C3604B 快削黄銅丸棒



切断品も対応(別途ご相談)

カドミウム50ppm以下


寸 法 mm		1本の質量 (kg/本)	寸 法 mm		1本の質量 (kg/本)
直径 D	定尺長さ		直径 D	定尺長さ	
10	4,000	2.6			
12	"	3.8			
14	"	5.2			
15	"	6.0			
16	"	6.8			
18	"	8.6			
19	"	9.6			
20	"	10.6			
21	"	11.7			
22	"	12.8			
24	"	15.3			
25	"	16.6			
26	"	17.9			
28	"	20.8			
30	"	23.8			
32	"	27.1			
34	"	30.6			
35	"	32.4			
36	"	34.3			
38	"	38.3			
40	"	42.4			
42	"	46.7			
45	"	53.6			
46	"	56.0			
48	"	61.0			
50	"	66.2			
54	"	77.5			
55	"	80.1			
60	"	96.0			

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# カドミフリー黄銅六角棒 (BsBM)

C3604B 快削黄銅棒

カドミウム50ppm以下




寸 法 mm		1本の質量 (kg/本)	寸 法 mm		1本の質量 (kg/本)
対辺 A	定尺長さ		対辺 A	定尺長さ	
14	4,000	5.8			
17	"	8.5			
19	"	10.6			
21	"	12.9			
22	"	14.2			
24	"	16.9			
26	"	19.8			
27	"	21.3			
32	"	30.0			
41	"	49.5			
50	"	73.0			

# カドミフリー黄銅4角棒 (BsBM)

C3604B 快削黄銅棒

カドミウム50ppm以下



切断品も対応(別途ご相談)

寸 法 mm		1本の質量 (kg/本)	寸 法 mm		1本の質量 (kg/本)
辺 A	定尺長さ		辺 A	定尺長さ	
30	4,000	30.4			
40	"	54.0			
50	"	84.3			

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。

# リン青銅板 (PBP)

C5191P C5210P

定尺寸法 180mm×1200mm


● 在庫品

板厚 mm	材 質				1枚の質量 (kg/枚)
	JIS C5191P PBP2-1/2H	JIS C5191P PBP2-H	JIS C5210P PBSP-H	JIS C5210P PBS-EH	
0.10	●	●	●		0.192
0.15	●		●	●	0.288
0.20	●	●	●		0.384
0.25		●	●		0.480
0.30	●	●	●	●	0.576
0.35			●	●	0.672
0.40	●	●	●	●	0.768
0.50	●	●	●	●	0.960
0.60	●	●	●		1.152
0.70	●	●	●		1.344
0.80	●	●	●		1.536
1.00	●	●	●		1.921
1.20	●	●	●		2.304
1.50	●	●	●		2.880
1.60	●		●		3.072
2.00	●	●	●		3.840
2.30		●			4.417
2.50	●				4.801
3.00	●	●			5.761
4.00	●	●			7.681
5.00		●			9.601
6.00		●			11.521

表記の質量はテーブル計算です。実際の商品は現物の実重量となります。

# リン青銅丸棒 (PBB/PbPBB)

● C5191 普通棒在庫品    ■ C5441 快削棒在庫品




切断品も対応(別途ご相談)

寸法 mm		材質		1本の質量 (kg/本)	寸法 mm		材質		1本の質量 (kg/本)
直径 D	定尺長さ	C5191	C5441		直径 D	定尺長さ	C5191	C5441	
2	2,000		■	0.058	36	2,000	●		18.72
3	"	●	■	0.130	38	"	●	■	20.86
4	"	●	■	0.231	40	"	●	■	23.11
5	"	●	■	0.361	42	"	●	■	25.48
6	"	●	■	0.520	45	"	●	■	29.25
7	"	●	■	0.708	50	"	●		36.11
8	"	●	■	0.924	55	"	●		43.69
9	"		■	1.17	60	"	●		52.00
10	"	●	■	1.44	65	"	●		61.03
11	"	●	■	1.75	70	"	●		70.78
12	"	●	■	2.08	75	"	●		81.25
13	"	●	■	2.44	80	"	●		92.44
14	"	●	■	2.83	85	"	●		104.36
15	"	●	■	3.25	90	"	●		117.00
16	"	●	■	3.70	95	"	●		130.36
17	"		■	4.17	100	"	●		144.44
18	"	●	■	4.68	110	"	●		174.77
19	"	●	■	5.21	120	"	●		207.99
20	"	●	■	5.78	130	"	●		244.10
21	"		■	6.37	140	"	●		283.10
22	"	●	■	6.99	150	"	●		324.99
23	"		■	7.64	160	"	●		369.77
24	"	●	■	8.32					
25	"	●	■	9.03					
26	"	●	■	9.76					
28	"	●	■	11.32					
30	"	●	■	13.00					
32	"	●	■	14.79					
35	"	●	■	17.69					

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。

# 青銅鑄物棒 (BC-6CB)

CAC406CB



切断品も対応 (別途ご相談)

寸 法 mm		1 mの質量 (kg/m)	寸 法 mm		1 mの質量 (kg/m)
直径 D	定尺長さ		直径 D	定尺長さ	
20	3,050	3.3	200	3,050	297.2
25	"	5.0	210	2,050	331.2
30	"	7.0	220	"	362.9
35	"	9.5	230	"	396.0
40	"	12.3	240	1,250	434.5
45	"	15.5	250	"	469.7
50	"	19.1	260	"	508.7
55	"	23.2	270	"	547.9
60	"	27.4	280	"	588.6
65	"	32.1	290	"	630.8
70	"	37.0	300	"	676.7
75	"	42.4			
80	"	48.3			
85	"	54.4			
90	"	60.8			
95	"	68.0			
100	"	75.2			
105	"	82.8			
110	"	90.6			
115	"	98.9			
120	"	107.5			
125	"	117.4			
130	"	126.8			
135	"	138.1			
140	"	147.6			
145	"	158.7			
150	"	168.9			
160	"	191.7			
170	"	216.7			
180	"	241.6			
190	"	269.5			

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。  
300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# 青銅鑄物板 (BC-6CP)

CAC406CP




切断品も対応 (別途ご相談)

寸 法 mm			1枚の質量 (Kg/枚)	1mの質量 (kg/m)
板厚 t	幅 W	定尺長さ		
10	215	3,050	65.6	21.8
12	"	"	77.6	25.8
17	"	"	107.4	35.7
22	"	"	137.3	45.6
27	"	"	167.1	55.5
32	"	"	196.9	65.4
37	"	"	226.8	75.3
42	"	"	256.6	85.3
47	"	"	286.5	95.2
52	"	"	316.3	105.1
57	"	"	346.1	115.0
62	"	"	376.0	124.9
72	"			144.8
82	"			164.6
92	"			184.4
102	"			204.2
112	"			224.1
122	"			243.9
132	"			263.7
142	"			283.6
152	"			303.4
162	"			323.2
172	"			343.0
182	"			362.9
192	"			382.7
202	"			402.5
215	"	2,050	869.2	428.3

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実費にプラスとなります

# 青銅鑄物管 (BC-6CT) 1

CAC406CT




切断品も対応(別途ご相談)

寸 法 mm			1 mの質量 (kg/m)	寸 法 mm			1 mの質量 (kg/m)	
外径 D	内径 d	定尺長さ		外径 D	内径 d	定尺長さ		
30	15	3,050	5.8	65	55	3,050	12.0	
	20	"	4.6	70	35	"	29.0	
35	15	"	8.2		40	"	26.4	
	20	"	7.0		45	"	23.7	
	25	"	5.6		50	"	20.6	
40	20	"	9.8		55	"	17.0	
	25	"	8.3		75	30	"	37.1
	30	"	6.5	35		"	34.4	
45	20	"	13.1	40		"	31.8	
	25	"	11.6	45		"	29.1	
	30	"	9.7	50		"	25.8	
	35	"	7.6	55		"	22.3	
50	20	"	16.6	80	40	"	37.7	
	25	"	15.1		45	"	35.0	
	30	"	13.3		50	"	31.8	
	35	"	11.0		55	"	28.1	
	40	"	8.6		60	"	24.1	
55	25	"	19.2		85	40	"	43.8
	30	"	17.4	45		"	41.2	
	35	"	15.2	50		"	37.8	
	40	"	12.6	55		"	34.2	
60	30	"	21.7	90		40	"	50.2
	35	"	19.4			45	"	47.6
	40	"	16.8		50	"	44.3	
	45	"	14.1		55	"	41.1	
	50	"	11.0		60	"	36.6	
65	30	"	26.3		70	"	27.5	
	35	"	24.0	95	45	"	54.7	
	40	"	21.5		65	"	39.5	
	45	"	18.9	100	40	"	64.6	
	50	"	15.6		50	"	58.6	

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# 青銅鑄物管 (BC-6CT) 2

CAC406CT




切断品も対応(別途ご相談)

寸 法 mm			1mの質量 (kg/m)	寸 法 mm			1mの質量 (kg/m)
外径 D	内径 d	定尺長さ		外径 D	内径 d	定尺長さ	
100	60	3,050	51.0	160	80	3,050	148.2
	70	"	42.0		100	"	124.0
	75	"	37.1		120	"	93.6
105	65	"	54.2		130	"	76.0
	70	"	49.5	170	80	"	176.4
110	60	"	66.4		100	"	149.7
	70	"	57.4		120	"	119.0
	85	"	41.8		140	"	81.2
	90	"	35.7	180	100	"	175.4
115	65	"	70.3		120	"	144.7
120	50	"	90.9		140	"	106.9
	60	"	83.3		160	"	68.4
	80	"	64.0	190	100	"	202.5
	90	"	52.6		120	"	171.8
	100	"	39.2	200	100	"	229.5
125	65	"	88.8		140	"	164.0
	75	"	80.1		160	"	121.1
130	60	"	104.0	210	100	"	261.7
	80	"	83.2		140	"	195.0
	100	"	58.5	220	120	"	262.7
135	80	"	95.4	230	130	"	279.8
140	70	"	115.0		175	"	183.6
	90	"	93.2	240	140	"	295.4
	100	"	79.3	250	150	"	309.2
	110	"	65.2	260	160	2,050	328.0
145	75	"	121.4	270	150	"	388.7
	95	"	97.8	280	170	"	384.0
150	80	"	126.0	290	180	"	401.0
	100	"	101.2	300	180	1,250	448.4
	120	"	70.4		220	2,050	338.4
	130	"	53.6				

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# 青銅鑄物棒 (BC-3CB)

CAC403CB



切断品も対応(別途ご相談)

寸 法 mm		1mの質量 (kg/m)	寸 法 mm		1mの質量 (kg/m)
直径 D	定尺長さ		直径 D	定尺長さ	
14	3,050	1.5	230	2,050	396.0
16	"	1.9	240	1,250	434.5
17	"	2.1	250	"	470.8
20	"	3.4	260	"	508.7
25	"	5.1	270	"	547.9
30	"	7.2	280	"	588.6
35	"	9.6	300	"	678.9
40	"	12.5			
45	"	15.7			
50	"	19.3			
55	"	23.4			
60	"	27.7			
65	"	32.4			
70	"	37.4			
75	"	42.7			
80	"	48.7			
85	"	54.8			
90	"	61.2			
100	"	75.7			
110	"	91.1			
120	"	108.0			
130	"	127.3			
140	"	148.2			
150	"	169.6			
160	"	192.4			
170	"	216.7			
180	"	242.4			
190	"	269.5			
200	"	298.1			
210	2,050	331.2			
220	"	362.9			

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。  
300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# 青銅鑄物板 (BC-3CP)

CAC403CP




切断品も対応 (別途ご相談)

寸 法 mm			1枚の質量 (Kg/枚)	1mの質量 (kg/m)
板厚 t	幅 W	定尺長さ		
10	215	3,050	65.6	21.8
12	"	"	77.6	25.8
17	"	"	107.4	35.7
22	"	"	137.3	45.6
27	"	"	167.1	55.5
32	"	"	196.9	65.4
37	"	"	226.8	75.3
42	"	"	256.6	85.3
47	"	"	286.5	95.2
52	"	"	316.3	105.1
57	"			115.0
62	"			124.9
72	"			144.8
82	"	2,050	334.0	164.6
92	"			184.4
102	"			204.2
112	"			224.1
122	"			243.9
132	"			263.7
142	"			283.6
152	"			303.4
162	"			323.2
172	"			343.0
182	"			362.9
192	"			382.7
202	"			402.5
215	"	2,050	869.2	428.3

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# 青銅鑄物管 (BC-3CT)

CAC403CT




切断品も対応(別途ご相談)

寸法 mm			1mの質量 (kg/m)	寸法 mm			1mの質量 (kg/m)
外径 D	内径 d	定尺長さ		外径 D	内径 d	定尺長さ	
35	15	3,050	8.4	120	90	3,050	53.0
40	20	"	10.1	130	80	"	84.7
45	20	"	13.4		100	"	59.6
50	25	"	15.5	140	70	"	116.4
55	25	"	19.6		100	"	81.2
	35	"	15.6		110	"	66.6
60	30	"	22.1	150	80	"	127.5
	40	"	17.3		100	"	102.6
65	30	"	26.7	160	100	"	125.4
	35	"	24.5		110	"	110.8
70	35	"	29.5		120	"	94.8
	45	"	24.1	170	80	"	174.6
75	40	"	32.3		120	"	119.0
	50	"	26.1	180	100	"	175.4
80	40	"	38.4		120	"	144.7
	45	"	35.5	190	120	"	171.8
	50	"	32.2		140	"	135.4
85	50	"	38.3	200	100	"	231.0
	55	"	34.7		140	"	164.0
90	40	"	50.9	210	100	"	263.3
	50	"	44.8	220	120	"	264.3
	60	"	37.2	230	130	"	279.8
	70	"	28.4	240	140	"	295.4
100	50	"	59.4	250	150	"	310.9
	60	"	51.9	260	150	2,050	349.9
	70	"	42.9	270	140	"	409.1
	75	"	37.8	280	150	"	429.1
110	60	"	67.3	300	180	1,250	455.4
	70	"	58.3		200	2,050	397.8
120	60	"	84.3				
	80	"	64.8				

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# リン青銅鑄物棒 (PBC-2CB)

CAC502CB



切断品も対応(別途ご相談)

寸 法 mm		1mの質量 (kg/m)	寸 法 mm		1mの質量 (kg/m)
直径 D	定尺長さ		直径 D	定尺長さ	
14	3,050	1.5	230	2,050	396.0
17	"	2.2	240	1,250	434.5
20	"	3.3	250	"	470.8
25	"	5.0	270	"	547.9
30	"	7.0	280	"	588.6
35	"	9.5	300	"	678.9
40	"	12.3			
45	"	15.5			
50	"	19.1			
55	"	23.2			
60	"	27.4			
65	"	32.1			
70	"	37.0			
75	"	42.7			
80	"	48.3			
85	"	54.4			
90	"	60.8			
95	"	68.5			
100	"	75.2			
110	"	90.6			
120	"	107.5			
130	"	126.8			
140	"	147.6			
150	"	169.6			
160	"	191.7			
170	"	216.7			
180	"	242.4			
190	"	269.5			
200	"	298.1			
210	2,050	331.2			
220	"	362.9			

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。  
300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# リン青銅鑄物板 (PBC-2CP)

CAC502CP




切断品も対応(別途ご相談)

寸 法 mm			1枚の質量 (Kg/枚)	1mの質量 (kg/m)
板厚 t	幅 W	定尺長さ		
10	215	3,050	65.6	21.8
12	"	"	77.6	25.8
17	"	"	107.4	35.7
22	"	"	137.3	45.6
27	"	"	167.1	55.5
32	"	"	196.9	65.4
37	"	"	226.8	75.3
42	"	"	256.6	85.3
47	"	"	286.5	95.2
52	"			105.1
57	"			115.0
62	"			124.9
72	"			144.8
82	"	2,050	334.0	164.6
92	"			184.4
102	"			204.2
112	"			224.1
122	"			243.9
132	"			263.7
142	"			283.6
152	"			303.4
162	"			323.2
172	"			343.0
182	"			362.9
192	"			382.7
202	"			402.5
215	"	2,050	869.2	428.3

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。  
300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# リン青銅鑄物管 (PBC-2CT)

CAC502CT




切断品も対応(別途ご相談)

寸 法 mm			1 mの質量 (kg/m)	寸 法 mm			1 mの質量 (kg/m)
外径 D	内径 d	定尺長さ		外径 D	内径 d	定尺長さ	
30	15	3,050	5.8	120	80	3,050	64.8
	20	"	4.6		90	"	53.0
35	15	"	8.4	130	80	"	86.2
	20	"	7.0		90	"	74.5
	25	"	5.8	140	70	"	115.0
40	20	"	9.8	150	80	"	127.5
	30	"	6.8		100	"	102.6
45	20	"	13.1	160	80	"	148.7
	30	"	9.8	170	100	"	149.7
	35	"	7.9	180	80	"	200.2
50	20	"	16.6		120	"	144.7
	25	"	15.5	190	120	"	171.8
	30	"	13.3	200	100	"	231.0
	40	"	8.4		120	"	200.4
55	20	"	21.1	140	"	164.0	
	25	"	19.2	210	150	"	176.2
	30	"	17.8	220	100	"	294.8
60	30	"	21.7	230	130	"	279.8
	40	"	17.3	240	140	"	295.4
65	35	"	24.5	250	150	"	310.9
70	35	"	29.0	270	170	2,050	343.7
	45	"	24.1	280	150	"	429.1
75	50	"	26.1	300	180	1,250	455.4
80	40	"	37.7				
	60	"	24.9				
90	40	"	50.2				
	60	"	37.4				
95	65	"	40.3				
100	50	"	58.6				
110	70	"	57.4				
120	60	"	83.3				

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります。

# 鉛青銅鑄物棒 (LBC-3CB)

CAC603CB



切断品も対応(別途ご相談)

寸 法 mm		1mの質量 (kg/m)	寸 法 mm		1mの質量 (kg/m)
直径 D	定尺長さ		直径 D	定尺長さ	
14	3,050	1.6			
17	"	2.3			
20	"	3.5			
25	"	5.2			
30	"	7.3			
35	"	9.8			
40	"	12.7			
45	"	16.1			
50	"	19.7			
55	"	24.0			
60	"	28.3			
65	"	33.1			
70	"	38.2			
75	"	43.7			
80	"	49.8			
90	"	62.6			
100	"	77.4			
110	"	93.2			
120	"	110.5			
130	"	130.2			
140	"	151.6			
150	"	173.4			
160	"	196.8			
170	"	221.5			
180	"	247.8			
190	"	275.6			
200	"	304.8			
220	2,050	371.0			
250	1,250	481.4			
280	"	601.8			
300	"	694.1			

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。  
300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# 鉛青銅鑄物板 (LBC-3CP)

CAC603CP




切断品も対応 (別途ご相談)

寸 法 mm			1枚の質量 (Kg/枚)	1mの質量 (kg/m)
板厚 t	幅 W	定尺長さ		
10	215			22.1
12	"	3,050	78.4	26.1
17	"			36.1
22	"	3,050	138.8	46.1
27	"			56.1
32	"	3,050	199.1	66.2
37	"			76.2
42	"	3,050	259.5	86.2
47	"			96.2
52	"			106.3
57	"			116.3
62	"			126.3
72	"			146.4
82	"	2,050	337.7	166.4
92	"			186.5
102	"			206.5
112	"			226.6
122	"			246.6
132	"			266.7
142	"			286.7
152	"			306.8
162	"			326.8
172	"			346.8
182	"			366.9
192	"			386.9
202	"			407.0
215	"	2,050	878.9	433.1

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実費にプラスとなります

# 鉛青銅鑄物管 (LBC-3CT)

CAC603CT




切断品も対応(別途ご相談)

寸 法 mm			1 mの質量 (kg/m)	寸 法 mm			1 mの質量 (kg/m)
外径 D	内径 d	定尺長さ		外径 D	内径 d	定尺長さ	
30	15	3,050	6.1	190	120	3,050	175.7
35	20	"	7.5	200	140	"	167.7
40	20	"	10.4	220	120	"	270.2
45	30	"	10.3	250	150	"	317.9
50	30	"	14.0	280	150	2,050	438.7
55	30	"	18.2	300	180	1,250	465.7
60	25	"	24.4				
	30	"	22.6				
	40	"	17.7				
65	30	"	27.3				
70	35	"	30.2				
	45	"	24.6				
75	35	"	35.7				
	50	"	26.7				
80	40	"	39.4				
	45	"	36.5				
	60	"	25.4				
90	50	"	46.0				
	60	"	38.3				
100	60	"	53.0				
	75	"	38.7				
110	60	"	68.8				
	70	"	59.6				
120	60	"	86.1				
	80	"	66.3				
130	80	"	86.6				
140	70	"	119.0				
150	80	"	130.4				
160	100	"	128.2				
170	100	"	153.0				
180	120	"	147.9				

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# アルミニウム青銅鑄物棒 (ALBC-3CB)



CAC703CB

切断品も対応(別途ご相談)

F:鍛造

寸 法 mm		1mの質量 (kg/m)	寸 法 mm		1mの質量 (kg/m)
直径 D	定尺長さ		直径 D	定尺長さ	
20	3,050	3.3	250	1,250	411.2
25	"	4.9	260	"	443.9
30	"	6.8	F 260	1,280	453.6
35	"	9.0	270	1,250	477.8
40	"	11.5	F 280	1,000	515.1
45	"	14.3	F 300	"	569.8
50	"	17.4			
55	"	20.9			
60	"	24.6			
65	"	28.6			
70	"	33.0			
75	"	37.7			
80	"	43.2			
85	"	48.5			
90	"	54.7			
95	"	60.7			
100	"	67.0			
110	"	80.4			
120	"	95.2			
130	"	111.1			
140	"	130.1			
150	"	148.7			
160	"	170.5			
170	"	191.6			
180	"	214.0			
190	"	237.7			
200	"	262.5			
210	2,050	290.0			
220	"	317.5			
F 230	1,640	357.2			
F 240	1,530	387.9			

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。  
300mm以下の長さ切断は、切断目減り分(5mm)のロスを実費にプラスとなります

# アルミニウム青銅鑄物板 (ALBC-3CP)

CAC703CP




切断品も対応 (別途ご相談)

寸 法 mm			1枚の質量 (Kg/枚)	1mの質量 (kg/m)
板厚 t	幅 W	定尺長さ		
10	215	3,050	58.4	19.4
12	"	"	69.0	22.9
17	"	"	95.5	31.7
22	"	"	122.0	40.5
27	"	"	148.5	49.4
32	"	"	175.1	58.2
37	"	"	201.6	67.0
42	"	"	228.1	75.8
47	"	"	254.6	84.6
52	"			93.4
57	"			102.2
62	"			111.0
72	"			128.7
82	"			146.3
92	"			163.9
102	"			181.5
112	"			199.2
122	"			216.8
132	"			234.4
142	"			252.0
152	"			269.7
162	"			287.3
172	"			304.9
182	"			322.5
192	"			340.2
202	"			357.8
300	300			739.3

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# アルミニウム青銅鑄物管 (ALBC-3CT)

CAC703CT




切断品も対応(別途ご相談)

寸 法 mm			1 mの質量 (kg/m)	寸 法 mm			1 mの質量 (kg/m)
外径 D	内径 d	定尺長さ		外径 D	内径 d	定尺長さ	
40	25	3,050	8.6	180	140	3,050	103.0
45	20	"	12.6	190	100	"	183.0
50	35	"	11.3		120	"	157.3
55	30	"	16.5	200	100	"	207.9
65	30	"	24.3		140	"	151.5
	45	"	18.0	210	120	"	208.3
70	35	"	26.9	220	140	"	204.1
	45	"	22.4	260	160	2,050	292.4
75	40	"	29.4	270	150	"	344.6
	50	"	24.3				
80	40	"	35.2				
85	40	"	40.5				
	55	"	32.4				
90	50	"	41.6				
	60	"	35.3				
100	40	"	58.9				
	60	"	47.6				
110	60	"	61.0				
	70	"	53.5				
	90	"	34.7				
120	60	"	75.8				
	100	"	38.1				
130	70	"	84.2				
	100	"	54.1				
140	90	"	85.4				
150	90	"	104.0				
	100	"	92.8				
160	80	"	136.6				
	100	"	115.8				
170	100	"	137.0				
180	120	"	133.7				

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります。

# アルミニウム青銅棒 (ABB2・1) 1

C6191B C6161B



切断品も対応(別途ご相談)


\*:ABB1 F:鍛造品

寸 法 mm		1mの質量 (kg/m)	寸 法 mm		1mの質量 (kg/m)
直径 D	定尺長さ		直径 D	定尺長さ	
*3	1,000	0.054	46	2,050	13.3
*4	"	0.096	48	"	14.5
*5	"	0.15	50	"	15.8
*6	2,000	0.23	55	"	19.0
*7	"	0.31	60	"	22.6
*8	"	0.41	65	"	26.5
*10	"	0.63	70	"	30.7
*12	"	0.91	75	"	35.3
*13	"	1.07	80	"	40.1
*14	"	1.24	85	"	45.2
*15	"	1.42	F 90	"	52.6
*16	"	1.62	F 95	"	58.5
16	2,050	1.7	F 100	"	64.7
18	"	2.1	F 105	"	71.2
20	"	2.6	F 110	"	78.0
22	"	3.1	F 115	"	85.1
23	"	3.4	F 120	"	94.1
24	"	3.7	F 130	"	110.0
25	"	4.0	F 135	"	118.4
26	"	4.3	F 140	"	127.1
28	"	5.0	F 150	"	146.5
30	"	5.7	F 160	"	165.2
32	"	6.5	F 170	"	186.0
34	"	7.3	F 180	"	208.2
35	"	7.8	F 190	"	231.5
36	"	8.2	F 200	"	256.2
37	"	8.7	F 205	"	268.9
38	"	9.1	F 210	"	282.0
40	"	10.1	F 220	"	309.1
42	"	11.1	F 230	"	337.5
45	"	12.8	F 240	"	371.6

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# アルミニウム青銅棒 (ABB2-1)2

C6191B C6161B



切断品も対応(別途ご相談)

F:鍛造品

寸 法 mm		1mの質量 (kg/m)	寸 法 mm		1mの質量 (kg/m)
直径 D	定尺長さ		直径 D	定尺長さ	
F 250	2,050	401.0			
F 260	1,050	437.2			
F 270	〃	471.0			
F 280	〃	506.0			
F 290	〃	542.2			
F 300	〃	583.5			
F 310	〃	622.5			

# アルミニウム青銅板 (ABP2)

C6191P




切断品も対応(別途ご相談)

F:鍛造品

寸 法 mm			1枚の質量 (Kg/枚)
板厚 t	幅 W	定尺長さ	
F 15	300	1,000	42.2
F 20	〃	〃	54.6
F 25	〃	〃	67.0
F 30	〃	〃	79.4
F 35	〃	〃	91.8
F 40	〃	〃	104.2
F 45	〃	〃	116.6
F 50	〃	〃	129.0

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# 電極用ベリリウム50合金銅棒 (BECUB-50A)



切断品も対応(別途ご相談)

F:鍛造品

寸 法 mm		1本の質量 (Kg/本)	寸 法 mm		1本の質量 (Kg/本)
直径 D	定尺長さ		直径 D	定尺長さ	
3.2	1,000	0.072	30	1,000	6.5
5	"	0.177	32	"	7.4
6	"	0.254	35	"	8.8
8	"	0.45	F 40	"	12.1
10	"	0.71	F 45	"	15.2
12	"	1.02	F 50	"	18.7
13	"	1.2	F 55	"	22.6
14	"	1.4	F 60	"	27.7
16	"	1.8	F 65	"	32.3
18	"	2.3	F 70	"	37.4
20	"	2.9	F 75	"	42.7
22	"	3.5	F 80	"	48.5
25	"	4.5	F 85	"	54.5
26	"	4.9	F 90	"	61.0
28	"	5.6	F 100	"	75.0

# 電極用ベリリウム50合金銅板 (BECUP-50A)




F:鍛造品

寸 法 mm			1枚の質量 (Kg/本)
板厚 t	幅 W	定尺長さ	
F 15	300	1,000	46.7
F 20	"	"	60.4
F 25	"	"	74.1
F 30	"	"	87.8
F 35	"	"	101.6
F 40	"	"	115.3
F 45	"	"	129.0
F 50	"	"	145.5
F 55	"	"	159.2
F 60	"	"	172.9

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります。

# 電極用クローム銅棒 (CRCUB)



切断品も対応(別途ご相談)

F: 鍛造品

寸法 mm		1本の質量 (Kg/本)	寸法 mm		1本の質量 (Kg/本)
直径 D	定尺長さ		直径 D	定尺長さ	
3	1,000	0.064	75	1,000	40.5
4	"	0.113	80	"	46.1
5	"	0.177	85	"	52.1
6	"	0.25	90	"	58.4
7	"	0.35	100	"	72.1
8	"	0.45	F 105	"	82.5
9	"	0.57	F 110	"	90.4
10	"	0.7	F 115	"	98.6
12	"	1.0	F 120	"	107.3
13	"	1.2	F 125	"	116.2
14	"	1.4	F 130	"	125.6
15	"	1.6	F 135	"	135.3
16	"	1.8	F 140	"	145.3
18	"	2.3	F 145	"	155.7
19	"	2.6	F 150	"	168.7
20	"	2.9	F 155	"	179.9
22	"	3.5	F 160	"	191.5
25	"	4.5	F 165	"	203.4
26	"	4.9	F 170	"	228.3
28	"	5.6	F 180	"	254.7
30	"	6.5	F 190	"	282.5
32	"	7.4	F 200	"	311.8
35	"	8.8			
38	"	10.4			
40	"	11.5			
45	"	14.6			
50	"	18.0			
55	"	21.8			
60	"	25.9			
65	"	30.4			
70	"	35.3			

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実質にプラスとなります

# 電極用クローム銅板 (CRCUP)



切断品も対応(別途ご相談)

F: 鍛造品

寸 法 mm			1枚の質量 (Kg/枚)
板厚 t	幅 W	定尺長さ	
1.0	200	1,000	1.8
1.5	"	"	2.7
2.0	"	"	3.6
3.0	"	"	5.4
4.0	300	"	10.8
5.0	"	"	13.5
6.0	"	"	16.2
8.0	"	"	21.6
10.0	"	"	27.0
12.0	"	"	32.4
15.0	"	"	40.5
F 15	400	"	62.7
F 20	"	"	81.2
F 25	"	"	99.6
F 30	"	"	118.1
F 35	"	"	136.5
F 40	"	"	155.0
F 45	"	"	173.4
F 50	"	"	195.6
F 55	"	"	214.0
F 60	"	"	232.5
F 65	"	"	250.9
F 70	"	"	269.4
F 80	"	"	306.3
F 90	"	"	343.2
F 100	"	"	380.1
F 110	320	"	325.4
F 120	"	"	354.2

表記の質量はテーブル計算です。実際の商品は現物の実質量となります。重量を表示している規格は標準在庫品です。300mm以下の長さ切断は、切断目減り分(5mm)のロスを実費にプラスとなります