
## ステンレスチャンネル(304/316/316L)

SUS304(熱間圧延品·溶接品)316/316L(溶接品)



● 溶接品 ▲ 6M圧延品、4M溶接品 1本の質量(Kg/本)

		一 / 公按吅		7.1.2.7.1.1	「本の貝里(Ng/本)		
寸 法mm			304		316·316L		
縦 H	横 B	肉厚 t	定尺長さ mm		定尺長さ mm	R1	R2
			4,000	6,000	6,000		
40	20	3.0		10.8		4.0	2.0
50	25	3.0		13.7		4.0	2.0
80	40	3.0		<b>22.3</b>		4.5	2.0
	40	5.0	24.0	35.9	36.1	4.5	3.0
100	50	3.0		<b>28.5</b>		6.5	2.0
	50	4.0	24.8	37.2	37.4	6.5	3.0
	50	5.0	30.6	45.9	46.2	6.5	3.0
	50	6.0	36.1	54.1	54.4	6.5	4.5
120	60	6.0		<b>65.4</b>		6.5	4.0
130	65	6.0	48.0	72.0	72.6	8.5	4.0
150	75	6.0	55.6	83.4	84.0	8.5	4.0
130	75	9.0	81.2	122.0	122.0	8.5	6.0
200	100	6.0	<b>•</b> 74.8	●112.0		10.0	5.0
	100	8.0	<b>9</b> 8.4	●148.0		10.0	6.0
	100	10.0	△121.0	△182.0	△ 183.0	10.0	7.0
主 コの紙具はこ	ブル KE 로 구 . 다 P	かっさし いきまち			山     		

## SUS304ワイドチャンネル

SUS304(溶接品)



						<u> </u>
	寸	法 mm	1本の質量	R1	R2	
縦 H	横 B	肉厚 t	定尺長さ	<b>(</b> kg/本)	IXI	1\2
220	65	6.0	6,000	97.8	8.5	4.0
230	65	6.0	"	100.0	8.5	4.0
250	75	6.0	"	112.0	10.0	5.0
	75	9.0	"	165.0	10.0	6.0
	90	9.0	"	178.0	10.0	6.0
	100	10.0	"	206.0	10.0	7.0
300	90	9.0	"	199.0	10.0	6.0
	90	10.0	"	220.0	10.0	7.0
	100	10.0	"	229.0	10.0	7.0
まれる所見けこ ブ		 므とけ思かる提合があ	<u> </u> ハキナ 手見をまこし	 		