

アルミ板定尺板2(A1100P)

A1100P H14

○ 国内材 ▲ 輸入材 □ B2アルマイト

板厚 mm	寸 法 mm											
	1000 x 2000				1000 x 3000				1250 x 2500			
	国内材	輸入材	B2アルマイト	1枚の質量 (kg/枚)	国内材	輸入材	B2アルマイト	1枚の質量 (kg/枚)	国内材	輸入材	B2アルマイト	1枚の質量 (kg/枚)
1.5	○	▲	□	8.13	○		□	12.2	○	▲	□	12.7
2.0	○	▲	□	10.84	○	▲	□	16.3	○	▲	□	16.9
2.5									○			21.2
3.0	○	▲	□	16.25					○	▲	□	25.4

表記の質量はテーブル計算です。実際の商品とは異なる場合があります。

アルミ板定尺板3(A1100P)

A1100P H14

○ 国内材 ▲ 輸入材

板厚 mm	寸 法 mm											
	1250 x 3050				1250 x 4000				1525 x 3050			
	国内材	輸入材		1枚の質量 (kg/枚)	国内材	輸入材		1枚の質量 (kg/枚)	国内材	輸入材		1枚の質量 (kg/枚)
1.5	○			15.5					○			18.9
2.0	○	▲		20.7		▲		27.10	○	▲		25.2
3.0												

表記の質量はテーブル計算です。実際の商品とは異なる場合があります。

アルミ定尺板4(A5052P・アルハイス・アルジェイド)

A5052P

○ H32又は34

△アルハイス

□ アルジェイド

板厚 mm	寸 法 mm							
	1000 × 2000				1250 × 2500			
	H32/H34	アルハイス	アルジェイド	1枚の質量 (kg/枚)	H32/H34	アルハイス	アルジェイド	1枚の質量 (kg/枚)
0.5	○			2.70				
0.8	○			4.29				
1.0	○			5.40	○			8.38
1.2	○			6.43	○			10.05
1.5	○			8.04	○			12.56
2.0	○			10.72	○			16.75
2.5	○			13.40	○			20.94
3.0	○			16.08	○			25.13
4.0		△	□	21.44		△	□	33.50
5.0		△	□	26.08		△	□	41.88
6.0		△	□	32.16		△	□	50.25
8.0		△	□	42.88		△	□	67.00
10.0		△	□	53.60		△	□	83.75
12.0		△	□	64.32		△	□	100.50
15.0		△	□	80.40		△	□	125.63
16.0		△	□	85.76		△	□	134.00
18.0		△	□	96.48		△	□	150.75
20.0		△	□	107.20		△	□	167.50
22.0		△	□	117.42		△	□	184.30
25.0		△	□	134.00		△	□	209.40
30.0		△	□	160.80		△	□	251.30
35.0		△	□	187.60				
40.0		△	□	214.40				
45.0			□	241.20				
50.0			□	268.00				
55.0			□	294.80				
60.0			□	321.60				


表記の質量はテーブル計算です。実際の商品とは異なる場合があります。

カラーアルミコイル

板厚 mm	0.40	0.50	0.60	0.80
幅 mm	914	914	914	914
m当りの質量(kg/m)	1.00	1.25	1.50	2.00
シルバー	○	○	○	○
ブロンズ	○		○	
ホワイト			○	
クリーム			○	
Dブラック改			○	

表記の質量はテーブル質量です。実際の商品とは異なる場合があります

アルミ丸管(引抜丸管)A1070TD・A5052TD



定尺 4,000mm


○ A1070TD

☆ A5052TD

外径 D mm	肉 厚 t mm								
	0.8	1.0	1.4	1.5	2.0	3.0	4.0	5.0	その他
6		○							
8	○	○	☆						
10		○	☆	○					
12		○ ☆			○				
12.7		○							
14		○			○				
15		○	☆						
16		○		○	○ ☆	☆			
17		○							
18		○		○					
19		○ ☆		○	○ ☆	○			
20		○	☆	○	○ ☆	☆			
22		○		○	○ ☆	☆			
25		○		○	○ ☆	○ ☆			☆ t=1.6
28					○ ☆	☆			☆ t=1.6
30		○	☆		○ ☆	○ ☆			
32					○ ☆	○ ☆			
35					○ ☆	○ ☆			
38					○ ☆	○ ☆	☆	☆	☆ t=3.75
40		○			○ ☆	○ ☆	○ ☆	☆	
42					○				
43				○					
45					○ ☆	○ ☆		○ ☆	
50				○	○ ☆	○ ☆	○ ☆	○ ☆	
55								☆	☆ t=8.0
60					☆	○ ☆	○ ☆	○ ☆	
65						○ ☆		○ ☆	
70						○ ☆		○ ☆	
75						○ ☆		○ ☆	
80						○ ☆	☆	○ ☆	
85								○	
90						○	☆	○ ☆	
100						○ ☆	○	○ ☆	
110						○		○ ☆	
120						○	☆	○ ☆	
130						○ ☆		○ ☆	
140								☆	
150						○		○ ☆	
165								○	

アルミ四角管(63角パイプ)

A6063-T5



寸 法 mm			1本の質量 (kg/本)	寸 法 mm			1本の質量 (kg/本)
辺 A	肉厚 t	定尺長さ		辺 A	肉厚 t	定尺長さ	
9	1.2	5,000	0.510				
10	1.0	"	0.485				
12	1.2	"	0.705				
15	1.2	"	0.900				
	1.5	"	1.095				
19	1.5	"	1.420				
20	1.5	"	1.500				
	2.0	"	1.945				
	2.5	"	2.365				
25	1.5	"	1.905				
	2.0	"	2.495				
	2.5	"	3.040				
30	1.5	"	2.310				
	2.0	"	3.025				
	3.0	"	4.375				
40	2.0	"	4.105				
	2.5	"	5.065				
	3.0	"	5.995				
50	2.0	"	5.185				
	2.5	"	6.415				
	3.0	"	7.615				
60	2.0	"	6.265				
	2.5	"	7.760				
70	2.0	"	7.345				
80	2.0	"	8.425				
	2.5	"	10.465				
100	2.5	"	13.165				
	3.0	"	15.715				

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ平角管(63平角パイプ)


A6063-T5



寸 法 mm				1本の 質量 (kg/本)	寸 法 mm				1本の 質量 (kg/本)	
辺 A	辺 B	肉厚 t	定尺長さ		辺 A	辺 B	肉厚 t	定尺長さ		
20	10	1.2	5,000	0.895	70	30	2.0	5,000	5.185	
	15	1.5	"	1.295		30	3.0	"	7.615	
25	15	1.5	"	1.505		50	2.0	"	6.265	
	15	2.0	"	1.945	80	40	2.0	"	6.265	
30	15	1.5	"	1.705		40	2.5	"	7.765	
	15	2.0	"	2.225		40	3.0	"	9.235	
	20	1.5	"	1.905	100	30	2.5	"	8.440	
	20	2.0	"	2.485		50	2.0	"	7.885	
	20	2.5	"	3.040		50	2.5	"	9.790	
	25	3.0	"	3.970		50	3.0	"	11.665	
40	20	1.5	"	2.310		80	2.7	"	12.760	
	20	2.0	"	3.035	110	40	2.0	"	7.915	
	20	2.5	"	3.715	120	60	2.8	"	13.190	
	20	3.0	"	4.375	150	50	2.5	"	13.165	
	25	3.0	"	4.780		50	3.0	"	15.715	
	50	30	1.5	"	2.780					
		30	2.0	"	3.565					
		30	3.0	"	5.185					
25		1.5	"	2.925						
60	25	2.0	"	3.835						
	30	2.0	"	4.105						
	25	2.0	"	4.375						
	30	1.5	"	3.535						
	30	2.0	"	4.650						
	30	2.5	"	5.740						
	40	2.0	"	5.185						
	40	2.5	"	6.415						
	40	3.0	"	7.615						
	40	4.0	"	9.935						

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ丸棒(1)




△ L=2000

○ L=4000

直径 D mm	材 質							A1070 1mの質量 (Kg/m)
	A1070 (1S)	A2017-T4 (17S)	A5052 (52S)	A5056 (56S)	A6061-T6 (61S)	C6PT8 (A2011) (11S相当)	A6063-T5 (63S)	
3	△		△					0.019
4	△		△					0.034
5	△	△	△			△		0.053
6	△	△	△			△		0.076
7	△	△	△			△		0.104
8	△	△	△	○		△	○	0.136
9	△	△	△			△	○	0.175
10	○	○	○	○	○	△	○	0.212
11	○	○	○			△		0.257
12	○	○	○	○		△	○	0.307
13	○	○	○	○			○	0.359
14	○	○	○	○		△		0.417
15	○	○	○	○		△	○	0.478
16	○	○	○	○	○	△	○	0.549
17	○	○	○	○				0.615
18	○	○	○	○				0.690
19	○	○	○	○	○			0.768
20	○	○	○	○	○		○	0.852
21		○						0.939
22	○	○	○	○			○	1.030
23		○						1.126
24		○						1.226
25	○	○	○	○	○		○	1.330
26	○	○	○	○				1.438
28	○	○	○	○				1.669
30	○	○	○	○	○		○	1.916
32	○	○	○	○	○		○	2.180
33		○						2.371
34		○						2.461
35	○	○	○	○	○			2.608
36	○	○	○	○				2.800
38	○	○	○	○				3.104
40	○	○	○	○	○		○	3.406
42	○	○	○	○	○			3.754
45	○	○	○	○	○		○	4.310
46		○						4.501
48		○	○	○				4.901
50	○	○	○	○	○		○	5.321

表記の質量はテーブル質量です。実際の商品とは異なる場合があります

アルミ丸棒(2)



▲ L=2000


○ L=4000

直径 D mm	材 質							A1070 1mの質量 (Kg/m)
	A1070 (1S)	A2017-T4 (17S)	A5052 (52S)	A5056 (56S)	A6061-T6 (61S)	C6PT8 (A2011) (11S相当)	A6063-T5 (63S)	
52		○						5.753
55	○	○	○	○	○			6.438
60	○	○	○	○	○		○	7.719
65	○	○	○	○	○			9.056
70	▲	○	▲	▲	▲			10.506
75	▲	○	▲	▲	▲			12.061
80	▲	○	▲	▲	▲			13.722
85	▲	○	▲	▲	▲			15.377
90	▲	○	▲	▲	▲			17.241
95	▲	○	▲	▲	▲			19.205
100	▲	○	▲	▲	▲			21.284
105		▲						23.550
110	▲	▲	▲	▲	▲			25.754
115		▲						28.013
120	▲	▲	▲	▲	▲			30.649
130	▲	▲	▲	▲	▲			35.963
140	▲	▲	▲	▲	▲			41.650
150	▲	▲	▲	▲	▲			47.800
160	▲	▲	▲	▲	▲			54.900
170		▲	▲	▲	▲			61.480
180		▲	▲	▲	▲			69.000
190		▲	▲	▲	▲			76.800
200		▲	▲	▲	▲			85.200
210		▲		▲	▲			93.820
220		▲		▲	▲			103.000
230		▲		▲	▲			112.600
240		▲		▲	▲			122.600
250		▲		▲	▲			133.000
260		▲		▲	▲			143.800
270		▲		▲	▲			156.700
280		▲		▲	▲			166.900
290		▲		▲				178.700
300		▲		▲	▲			191.600
310		▲		▲				204.500
320		▲		▲				217.900
330		▲		▲				231.700
340		▲		▲				246.000
350		▲		▲				260.700

表記の質量はテーブル質量です。実際の商品とは異なる場合があります

アルミ四角棒 (63角棒)

A6063-T5




寸 法 mm		1本の質量 (kg/本)	寸 法 mm		1本の質量 (kg/本)
辺 A	定尺長さ		辺 A	定尺長さ	
5	4,000	0.272			
6	"	0.388			
7	"	0.524			
8	"	0.692			
9	"	0.876			
10	"	1.080			
12	"	1.556			
13	"	1.824			
14	"	2.116			
15	"	2.432			
16	"	2.764			
18	"	3.512			
19	"	3.900			
20	"	4.336			
22	"	5.220			
25	"	6.776			
30	"	9.720			
32	"	11.060			
35	"	13.232			
38	"	15.596			
40	"	17.344			
45	"	21.872			
50	"	27.000			
55	"	32.672			
60	L=3000	29.160			

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ平角棒 (63平角棒) 1

A6063-T5




寸 法 mm			1本の 質量 (kg/本)	寸 法 mm			1本の 質量 (kg/本)	寸 法 mm			1本の 質量 (kg/本)
厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ	
2	10	4,000	0.216	4	60	4,000	2.592	8	15	4,000	1.296
	12	"	0.260		70	"	3.024		20	"	1.728
	15	"	0.324		10	"	0.540		25	"	2.160
	20	"	0.432	5	15	"	0.812		30	"	2.592
	25	"	0.540		20	"	1.084		32	"	2.772
	30	"	0.648		25	"	1.352		35	"	3.024
	35	"	0.756		30	"	1.620		40	"	3.456
	40	"	0.864		35	"	1.892		50	"	4.320
	50	"	1.080		40	"	2.160		60	"	5.184
3	10	"	0.324		50	"	2.700	75	"	6.480	
	12	"	0.388		60	"	3.240	100	"	8.640	
	15	"	0.488		70	"	3.780	9	20	"	1.944
	16	"	0.520	75	"	4.052	30		"	2.916	
	20	"	0.648	100	"	5.400	40		"	3.888	
	25	"	0.812	10	"	0.648	50		"	4.860	
	30	"	0.972	12	"	0.776	60		"	5.832	
	35	"	1.136	15	"	0.976	75		"	7.292	
	40	"	1.296	20	"	1.296	100		"	9.720	
50	"	1.620	25	"	1.620	10	15		"	1.620	
60	"	1.944	30	"	1.944		20		"	2.168	
70	"	2.268	32	"	2.076		25	"	2.700		
4	10	"	0.432	6	35		"	2.268	30	"	3.240
	12	"	0.520		40		"	2.592	35	"	3.780
	15	"	0.648		45		"	2.916	40	"	4.320
	20	"	0.868		50		"	3.240	45	"	4.860
	25	"	1.080		60		"	3.888	50	"	5.420
	30	"	1.300		65		"	4.212	60	"	6.480
	40	"	1.728		75	"	4.860	70	"	7.560	
	50	"	2.160		100	"	6.480	75	"	8.132	

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ平角棒 (63平角棒) 2

A6063-T5




寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)
厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ		厚さA	幅 B	定尺長さ	
10	80	4,000	8.640	20	65	4,000	14.040				
	100	"	10.840		70	"	15.120				
	120	"	12.960		80	"	17.280				
	125	"	13.500		100	"	21.680				
	150	"	16.200		150	"	32.400				
12	20	"	2.592	25	30	"	8,100				
	25	"	3.240		35	"	9.452				
	30	"	3.888		40	"	10.800				
	40	"	5.180		50	"	13.500				
	50	"	6.504		60	"	16.200				
	60	"	7.776		80	"	21.600				
	75	"	9.720		100	"	27.000				
	100	"	12.960	30	40	"	12.960				
	120	"	15.552		50	"	16.200				
15	20	"	3.252	30	60	"	19.440				
	25	"	4.052		65	"	21.060				
	30	"	4.860		75	"	24.300				
	40	"	6.480		100	"	32.400				
	50	"	8.100	35	40	"	15.120				
	60	"	9.720		50	"	18.900				
	75	"	12.148		60	"	22.680				
	100	"	16.200		85	"	32.132				
150	"	24.300	100	2,500	23.625						
20	25	"	5.400	40	50	4,000	21.600				
	30	"	6.504		60	"	25.920				
	35	"	7.560		75	"	32.400				
	40	"	8.672		100	2,500	27.000				
	50	"	10.800								
	60	"	12.960								

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミチャンネル(63チャンネル)


A6063-T5

Rナシチャンネル



寸 法 mm				1本の質量 (kg/本)	寸 法 mm				1本の質量 (kg/本)
A	B	肉厚 t	定尺長さ		A	B	肉厚 t	定尺長さ	
10	10	1.6	5,000	0.580	50	25	3.0	5,000	3.805
15	15	1.5	"	0.860	60	30	3.0	"	4.615
	15	2.0	"	1.105	75	40	3.2	"	6.425
18	10	2.0	"	0.920		50	5.0	"	11.140
20	20	2.0	"	1.515	80	40	4.0	"	8.210
25	15	2.0	"	1.375	100	50	5.0	"	12.825
	25	2.0	"	1.915	125	65	6.0	"	19.685
30	15	2.0	"	1.510					
	25	3.0	"	2.995					
	30	2.4	"	2.765					
35	20	2.4	"	2.275					
40	20	2.0	"	2.050					
	20	3.0	"	2.995					
50	25	2.5	"	3.205					

R付きチャンネル




寸 法 mm				1本の質量 (kg/本)	R1	R2
A	B	肉厚 t	定尺長さ			
75	40	6.0	5,000	11.585	5.0	5.0
100	50	5.0	"	12.745	3.0	5.0
125	65	6.0	"	19.845	6.0	3.0
150	75	8.0	"	30.76	8.0	7.0

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ等辺アングル Rナシ (63アングル)

A6063-T5




寸 法 mm			1本の質量 (kg/本)	寸 法 mm			1本の質量 (kg/本)
辺 A	厚さ t	定尺長さ		辺 A	厚さ t	定尺長さ	
9	1.0	4,000	0.184	40	2.0	4,000	1.684
10	1.0	"	0.204		3.0	"	2.496
	1.2	"	0.244		4.0	"	3.284
12	1.2	"	0.296		5.0	"	4.052
15	1.0	"	0.312		6.0	"	4.796
	1.5	"	0.464	50	1.5	"	1.596
	2.0	"	0.604		3.0	"	3.144
	3.0	"	0.872		4.0	"	4.148
19	1.0	"	0.400		5.0	"	5.132
	1.5	"	0.592	6.0	"	6.092	
20	1.5	"	0.624	60	5.0	"	6.212
	2.0	"	0.820		6.0	"	7.388
	3.0	"	1.200	65	6.0	"	8.036
25	1.0	"	0.528		8.0	"	10.540
	1.2	"	0.636	70	4.0	"	5.876
	1.5	"	0.784	75	6.0	"	9.332
	2.0	"	1.036		9.0	"	13.704
	3.0	"	1.524	80	8.0	"	13.132
	4.0	"	1.988	100	10.0	"	20.520
	5.0	"	2.432				
30	1.0	"	0.636				
	1.2	"	0.764				
	1.5	"	0.948				
	2.0	"	1.256				
	3.0	"	1.848				
	4.0	"	2.420				
35	5.0	"	2.980				
	3.0	"	2.172				
	4.0	"	2.852				

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ不等辺アングル Rナシ (63アングル)

A6063-T5




寸 法 mm				1本の質量 (kg/本)
辺 A	辺 B	厚さ t	定尺長さ	
15	10	1.5	4,000	0.380
	10	2.0	〃	0.496
20	10	1.5	〃	0.464
	15	1.5	〃	0.540
	15	2.0	〃	0.712
25	15	1.5	〃	0.624
	15	2.0	〃	0.820
	15	3.0	〃	1.200
	20	2.0	〃	0.928
30	10	1.5	〃	0.624
	15	1.5	〃	0.704
	15	2.0	〃	0.928
	15	3.0	〃	1.360
	20	2.0	〃	1.036
	20	3.0	〃	1.524
40	10	1.5	〃	0.788
	20	2.0	〃	1.252
	20	3.0	〃	1.848
	30	3.0	〃	2.172
50	25	3.0	〃	2.332
	35	4.0	〃	3.500
60	40	5.0	〃	5.132
	50	5.0	〃	5.672
75	50	5.0	〃	6.480

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミアングル R付き (63アングル)


A6063-T5

等辺アングル



寸 法 mm			1本の質量 (kg/本)	R1	R2
辺 A	厚さ t	定尺長さ			
30	3.0	4,000	1.864	4.0	2.0
40	3.0	〃	2.524	4.5	2.0
	5.0	〃	4.056	4.5	3.0
	6.0	〃	4.836	6.0	3.0
50	5.0	〃	5.240	6.5	3.0
	6.0	〃	6.096	6.5	4.5
60	6.0	〃	7.484	8.5	4.0
65	6.0	〃	8.128	8.5	4.0
	8.0	〃	10.616	8.0	4.0
75	6.0	〃	9.456	6.0	3.0
	9.0	〃	13.804	8.5	4.0
80	8.0	〃	13.228	8.5	4.0
100	10.0	〃	20.640	8.5	4.0

不等辺アングル



寸 法 mm				1本の質量 (kg/本)	R1	R2
辺 A	辺 B	厚さ t	定尺長さ			
75	50	5.0	4,000	6.508	5.0	2.5
100	70	4.0	〃	7.256	5.0	-
	75	10.0	〃	17.936	10.0	5.0
125	75	12.0	〃	24.532	12.0	6.0

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。