








# カラーステンレス(ナスコート)

表面塗装:シリコン変成ポリエステル樹脂2度塗り2度焼き付け 厚さ20 $\mu$

板厚 mm		0.30			0.35		0.4		0.5	0.6
幅 mm		365	455	914	455	914	455	914	914	914
重量 (kg/m)		0.87	1.10	2.20	1.28	2.55	1.45	2.90	3.65	4.40
ML01 艶消しブラック	遮熱 塗装	○	○	○	○	○	○	○	○	
MN01 艶消しブラウン	遮熱 塗装		○	○	○	○	○	○		○
MZ01 艶消しグレー	遮熱 塗装				○	○		○	○	○
MG02 艶消し緑青	遮熱 塗装		○	○	○	○	○	○		
MG01 艶消しグリーン	遮熱 塗装			○	○	○		○		
PM20 カパーブラウン	遮熱 塗装				○	○				
PV19 キャメルブラウン	遮熱 塗装				○	○				
PZ45 メタリックグレー			○	○	○	○	○	○		
PZ01 シルバー		○	○	○	○	○	○	○	○	○
PV01 クリーム				○		○		○		
PW01 ホワイト				○		○		○		

# SUS304配管パイプ

SUS304TP-A




1本の質量(kg/本)

外径 D mm	呼び径		肉 厚 t mm 定尺4,000mm(一部6,000mmあり)										
	A	B	1.5	2.0	2.5	3.0	3.5	4.0	5.0	5.2	5.5	6.0	6.5
10.5	6	1/8	1.34	1.69									
13.8	8	1/4	1.84	2.35		3.23							
17.3	10	3/8	2.36	3.05	3.69	4.28							
21.7	15	1/2	3.02	3.92	4.80	5.60							
27.2	20	3/4	3.84	5.04	6.16	7.24							
34.0	25	1	4.84	6.36	7.84	9.28	10.6	12.0					
42.7	32	1 1/4	6.16	8.12	10.00	11.9	13.7	15.4					
48.6	40	1 1/2	7.04	9.28		13.6	15.7	17.8					
60.5	50	2	8.80	11.60		17.2	19.9	22.5	27.6		30.2		
76.3	65	2 1/2		14.80		21.9	25.4	28.8	35.5	36.8		42.0	
89.1	80	3		17.40		25.7		33.9	42.0		46.0	49.6	
101.6	90	3 1/2		19.80		29.5		38.9	48.0			57.2	
114.3	100	4		22.40		33.3		44.0	54.4			64.8	
139.8	125	5		27.50		40.8	47.6	54.0	67.2			80.0	
165.2	150	6				48.4	56.4	64.4	80.0			95.2	
216.3	200	8				63.6		84.8	105.0			126.0	136.0
267.4	250	10				79.2	92.0	105.0	131.0			156.0	169.0
318.5	300	12				94.4		125.0	156.0			187.0	202.0
355.6	350	14						140.0	175.0			209.0	
406.4	400	16						161.0	201.0			240.0	
457.2	450	18						181.0	226.0			270.0	

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。重量を表示している規格は標準在庫品です。

# SUS304化粧管(#400/HL) 4M

定尺4,000mm




○ #400

■ HL

外径 D mm	肉 厚 t mm					
	0.8	1.0	1.2	1.5	2.0	3.0
5.0	○	○				
6.0	○	○				
7.0	○	○				
8.0	○	○ ■				
9.0	○	○				
10.0	○	○ ■				
12.0	○	○ ■				
13.0	○	○ ■	○ ■	○ ■		
13.8			○ ■	○ ■		
14.0	○	○				
15.0	○	○				
16.0	○	○ ■	○ ■	○ ■	○ ■	
17.3				○ ■	○ ■	
19.0	○	○ ■	○ ■	○ ■	○ ■	
21.7		○	○ ■	○ ■	○ ■	○ □
22.0	○	○ ■	○ ■	○ ■	○ ■	
25.0	○	○ ■	○ ■	○ ■	○ ■	○ ■
25.4			○	○ ■	○ ■	
27.2		○ ■	○ ■	○ ■	○ ■	○ ■
32.0		○ ■	○ ■	○ ■	○ ■	○ ■
34.0		○	○ ■	○ ■	○ ■	○ ■
38.0		○	○ ■	○ ■	○ ■	○ ■
42.7			○ ■	○ ■	○ ■	○ ■
45.0				○ ■	○ ■	
48.6			○ ■	○ ■	○ ■	○ ■
50.0		○	○ ■	○ ■	○ ■	○ ■
60.5				○ ■	○ ■	○ ■
76.3				○ ■	○ ■	○ ■
89.1				○ ■	○ ■	○ ■
101.6				○ ■	○ ■	○ ■
114.3					○ ■	○ ■
139.8					○ ■	○ ■
165.2						○ ■
216.3						○ ■

# SUS304化粧管(#400/HL) 5M/6M

定尺5,000mm/6,000mm



○ #400

■ HL

外径 D mm	長さ mm	肉 厚 t mm		
		1.5	2.0	3.0
13.0	5,000	○ ■		
	6,000	○ ■		
16.0	5,000	○ ■		
	6,000	○ ■		
17.3	5,000	○ ■	○ ■	
	6,000	○ ■	○ ■	
19.0	5,000	○ ■	○ ■	
	6,000	○ ■	○ ■	
21.7	5,000	○ ■	○ ■	○ ■
	6,000	○ ■	○ ■	○ ■
22.0	5,000	○ ■		
	6,000	○ ■		
25.0	5,000	○ ■	○ ■	
	6,000	○ ■	○ ■	
27.2	5,000	○ ■	○ ■	○ ■
	6,000	○ ■	○ ■	○ ■
32.0	5,000	○ ■	○ ■	○ ■
	6,000	○ ■	○ ■	○ ■
34.0	5,000	○ ■	○ ■	○ ■
	6,000	○ ■	○ ■	○ ■
38.0	5,000	○ ■	○ ■	○ ■
	6,000	○ ■	○ ■	○ ■
42.7	5,000	○ ■	○ ■	○ ■
	6,000	○ ■	○ ■	○ ■
48.6	5,000	○ ■	○ ■	○ ■
	6,000	○ ■	○ ■	○ ■
50.0	5,000	○ ■	○ ■	○ ■
	6,000	○ ■	○ ■	○ ■
60.5	5,000	○ ■	○ ■	○ ■
	6,000	○ ■	○ ■	○ ■
76.3	5,000	○ ■	○ ■	○ ■
	6,000	○ ■	○ ■	○ ■
89.1	5,000			
	6,000		○ ■	○ ■
101.6	5,000			
	6,000		○ ■	○ ■
114.3	5,000			
	6,000		○ ■	○ ■
139.8	5,000			
	6,000		○ ■	○ ■
165.2	5,000			
	6,000			○ ■
216.3	5,000			
	6,000			○ ■

# SUS304角パイプ(四角管)


SUS304 未研磨/#400研磨/HL研磨

△ 未研磨

● #400

□ HL

**6** : 長さ6000mmあり




寸 法 mm		肉 厚 t mm				
辺 A	定尺長さ	1.0	1.2	1.5	2.0	3.0
7	4,000	● □				
9	3,000・4,000	△ ● □				
10	4,000	△ ● □	△ ● □			
12	"	△ ● □	△ ● □			
13	"	△ ● □	△ ● □			
14	"	△ ● □	△ ● □	△ ● □		
16	5,000	△ ● □	△ ● □	<b>△6 ●6 □6</b>		
19	"	△ ● □	△ ● □	<b>△6 ●6 □6</b>	△ ● □	
20	"		△ ● □	<b>△6 ●6 □</b>		
21	"	△ ● □	△ ● □	△ ● □		
22	"	△ ● □	△ ● □	△ ● □		
24	"	△ ● □	△ ● □	△ ● □		
25	"		<b>△6 ●6 □</b>	<b>△6 ●6 □6</b>		
25.4	"		△ ● □	△ ● □		
28.6	"	△ ● □	△ ● □	△ ● □		
30	"		<b>△6 ●6 □</b>	<b>△6 ●6 □6</b>	△ ● □	
32	"		△ ● □	<b>△6 ●6 □6</b>	△ ● □	
35	"		△ ● □	△ ● □		
38.5	"		△ ● □	△ ● □	△ ● □	
40	"			<b>△6 ●6 □6</b>	<b>△6 ●6 □6</b>	
41	"		△ ● □	<b>△6 ●6 □6</b>	△ ● □	
46	"			△ ● □	△ ● □	
50	"			<b>△6 ●6 □6</b>	<b>△6 ●6 □6</b>	<b>△6 ●6 □6</b>
60	"			<b>△6 ●6 □6</b>	<b>△6 ●6 □6</b>	△ ● □
75	"				<b>△6 ●6 □6</b>	<b>△6 ●6 □</b>
100	"				<b>△6 ●6 □6</b>	△ ● □



# SUS304角パイプ(平角管)

SUS304 未研磨/#400研磨/HL研磨


△ 未研磨    ● #400    □ HL    **6** : 長さ6000mmあり



寸 法 mm			肉 厚 t mm				
辺 A	辺 B	定尺長さ	1.0	1.2	1.5	2.0	3.0
19	10	4,000	△ ● □	△ ● □			
22	12	5,000	△ ● □	△ ● □	△ ● □		
24	14	"	△ ● □	△ ● □	△ ● □	△ ● □	
25	12	"		△ ● □	△ ● □		
30	20	"		△ ● □	<b>△6●6□6</b>		
	25	"		△ ● □	△ ● □		
32	16	"	△ ● □	△ ● □	<b>△6●6□6</b>		
40	18	"	△ ● □	△ ● □	△ ● □		
	20	"		△ ● □	<b>△6●6□6</b>	△ ● □	
	25	"		△ ● □	<b>△6●6□6</b>	△ ● □	
50	20	"		△ □	△ ● □	△ ● □	
	25	"			<b>△6●6□6</b>	△ ● □	
	30	"			<b>△6●6□6</b>	△ ● □	
51	26	"		△ ● □	<b>△6●6□6</b>	△ ● □	
60	25	"			△ ● □	△ ● □	
	30	"			<b>△6●6□6</b>	<b>△6●6□6</b>	
	40	"			△ ● □	△ ● □	△ ● □
61	32	"			<b>△6●6□6</b>	△ ● □	
65	18	"		△ ● □	△ ● □		
70	25	"			△ ● □	△ ● □	
	30	"			△ ● □	△ ● □	
75	45	"			<b>△6●6□6</b>	<b>△6●6□6</b>	△ ● □
80	40	"			<b>△6●6□6</b>	<b>△6●6□6</b>	△ ● □
90	30	"			<b>△6●6□6</b>	△ ● □	△ ● □
	50	"				△ ● □	△ ● □
100	40	"				△ ● □	△ ● □
	50	"				<b>△6●6□6</b>	<b>△6●6□6</b>
120	60	"				△ ● □	△ ● □
125	75	"				△ ● □	△ ● □
150	50	"				△ ● □	△ ● □

# ステンレス等辺アンゲル(304/316/316L/430) 1

SUS304/316/316L/430(熱間圧延品)




■ 全面HL、外2面#400研磨もあり    ○ 外2面#400研磨もあり    △ 全面HL研磨もあり    1本の質量(Kg/本)

寸法 mm		304			316・316L		430
辺 A	厚さ t	定尺長さ mm			定尺長さ mm		定尺長さ mm
		4,000	5,000	6,000	4,000	6,000	4,000
20	3	■ 3.58			3.60		○ 3.47
25	3	■ 4.52			4.56		○ 4.40
30	2						○ 3.62
	3	■ 5.48	6.85	■ 8.22		8.28	○ 5.32
	4			10.6			
	5			13.1			
	6			15.2			
35	3			9.66			
	4	8.40		12.6			
	6			18.2			
40	2						○ 4.88
	3	■ 7.40	9.25	■ 11.1		11.2	○ 7.20
	4	■ 9.64		■ 14.5			
	5	△ 11.9	14.9	■ 17.9		18.0	
	6	14.0		△ 21.0			
45	4			16.6			
	5			20.5			
50	3	△ 9.48		△ 14.2			
	4	△ 12.4	15.4	■ 18.5		18.7	
	5	△ 15.2	19.0	■ 22.9		23.0	
	6	△ 17.9	22.4	■ 26.9		27.0	
	8			34.7			
	9	25.8		△ 38.6			
60	5			27.6			
	6			■ 32.6			
65	5			30.3			
	6	△ 23.9	29.8	■ 35.8		36.1	
	8			46.4			
	9			51.8			

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

# ステンレス等辺アングル(304/316/316L/430) 2

SUS304/316/316L/430(熱間圧延品)



■ 全面HL、外2面#400研磨もあり

△ 全面HL研磨もあり

1本の質量(Kg/本)

寸法 mm		304			316・316L		430
辺 A	厚さ t	定尺長さ mm			定尺長さ mm		定尺長さ mm
		4,000	5,000	6,000	4,000	6,000	4,000
70	5			32.7			
	7			44.5			
75	5			35.0			
	6	△ 27.7	34.6	■ 41.5		41.8	
	8			54.1			
	9	△ 40.4		■ 60.6		60.6	
80	6			44.4			
	8			△ 57.8			
	10			70.8			
90	6			50.2			
	8			66.0			
	9	49.2		△ 73.8			
	10			81.0			
	12			96.0			
100	6	37.3	46.6	■ 55.9			
	8	48.8		△ 73.2			
	9			82.2			
	10	△ 60.4		■ 90.6		91.2	
	12			107.0			
125	9			103.0			
	12			136.0			
	15			167.0			
130	12			142.0			
150	9			125.0			
	12			165.0			
	15			203.0			

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。










# ステンレス四角棒(304/316/316L)

SUS304/316/316L

○ 304

■ 316/316L




寸 法 mm		1本の質量(kg/本)		表 面			
辺 A	定尺長さ	304	316・316L	HOT	COLD	HL	#400
3	2,000	0.142			○		
4	4,000	0.508			○		
5	"	0.792			○	○	
6	"	1.14			○	○	
7	"	1.56			○	○	
8	"	2.03			○	○	○
9	"	2.57			○	○	○
10	"	3.17		○	○	○	○
12	"	4.56		○	○	○	○
13	"	5.36		○	○	○	○
14	"	6.20		○	○	○	○
15	"	7.12		○	○	○	○
16	"	8.12		○	○	○	○
19	"	11.4	11.5	○ ■	○	○	○
20	"	12.7	12.8	○ ■	○	○	○
22	"	15.4	15.4	○ ■	○	○	
25	"	19.8	20.0	○ ■	○	○	○
26	"	21.4			○		
28	"	24.9		○	○	○	
30	"	28.6	28.7	○ ■	○	○	
32	"	32.5	32.7	○ ■	○	○	
36	"	41.2	41.4	○ ■	○		
38	"	46.0	46.0	○ ■	○	○	
40	"	50.8	51.2	○ ■	○		
42	"	56.0	56.4	○ ■			
45	"	64.4	64.8	○ ■	○	○	
50	"	79.2	80.0	○ ■	○	○	
55	"	96.0		○	○	○	
60	"	114.0		○	○	○	
65	"	134.0		○	○	○	
70	"	156.0		○			
75	"	178.0		○			
90	"	257.0		○			
100	"	317.0		○			

表記の質量はテーブル質量です。実際の商品とは異なる場合があります



# SUS304フラットバー 1

SUS304 FB HOT/ COLD/HL/#400研磨




スリットの酸洗肌

寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400		
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間	スリット
2	6	2,000	0.190			○			3	38	4,000	3.62	<input type="checkbox"/>	○	○	○	○		
	8	"	0.254			○				40	"	3.81	<input type="checkbox"/>	○	○	○	○	○	
	9	"	0.286			○				42	"	4.00			○	○			
	10	"	0.318			○				45	"	4.28	<input type="checkbox"/>	○	○	○	○		
	10	3,000	0.477							48	"	4.56			○	○			
	10	4,000	0.636		○	○	○			50	"	4.76	<input type="checkbox"/>	○	○	○	○	○	
	12	"	0.760			○				60	"	5.72	<input type="checkbox"/>	○	○	○	○	○	
	15	"	0.952		○	○	○			65	"	6.20	<input type="checkbox"/>	○	○	○	○		
	20	"	1.27		○	○	○			75	"	7.12		○	○	○	○	○	
	25	"	1.58		○	○	○			90	"	8.56			○				
	30	"	1.90		○	○	○			100	"	9.52		○	○	○	○	○	
	32	"	2.03		○	○	○			110	"	10.5			○				
	35	"	2.22		○					120	"	11.4			○				
	38	"	2.41		○	○				125	"	11.9			○				
	40	"	2.54		○	○	○			130	"	12.4			○				
45	"	2.86		○	○	○		140	"	13.3			○						
50	"	3.17		○	○	○		150	"	14.3			○						
3	5	3,000	0.357			○			4	9	"	1.14			○				
	6	4,000	0.572			○				10	"	1.27			○	○			
	7	"	0.668			○				11	"	1.40		○	○	○			
	8	"	0.760			○				12	"	1.52			○				
	9	"	0.856			○				13	"	1.65		○	○	○			
	10	"	0.952		○	○	○			15	"	1.90	○	○	○	○	○	○	
	12	"	1.14	<input type="checkbox"/>	○	○	○			16	"	2.03	○	○	○	○	○		
	13	"	1.24		○	○	○			17	"	2.16			○				
	15	"	1.43	<input type="checkbox"/>	○	○	○	○		19	"	2.41	○	○	○	○	○		
	16	"	1.52		○	○	○			20	"	2.54	○	○	○	○	○	○	
	19	"	1.81	<input type="checkbox"/>	○	○	○			22	"	2.79	○	○	○	○	○		
	20	"	1.90	<input type="checkbox"/>	○	○	○	○		25	"	3.17	○	○	○	○	○	○	
	22	"	2.09		○	○	○			30	"	3.81	○	○	○	○	○	○	
	25	"	2.38	<input type="checkbox"/>	○	○	○	○		32	"	4.08	○	○	○	○	○	○	
	30	"	2.86	<input type="checkbox"/>	○	○	○	○		35	"	4.44	○	○	○	○	○		
32	"	3.04	<input type="checkbox"/>	○	○	○	○	38	"	4.84	○	○	○	○	○	○			
35	"	3.33	<input type="checkbox"/>	○	○	○		40	"	5.08	○	○	○	○	○	○			

# SUS304フラットバー 2


SUS304 FB HOT/ COLD/HL/#400研磨



寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400		
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間	スリット
4	45	4,000	5.72	○	○	○	○		6	10	4,000	1.90			○	○			
	50	"	6.36	○	○	○	○	○		12	"	2.28			○	○			
	60	"	7.60	○	○	○	○	○		13	"	2.48			○	○			
	65	"	8.24	○	○	○	○			15	"	2.86	○	○	○	○	○	○	
	75	"	9.52	○	○	○	○	○		16	"	3.04			○	○			
	90	"	11.4			○	○			18	"	3.42			○	○			
	100	"	12.7		○	○	○	○		19	"	3.62	○	○	○	○			
5	8	"	1.27			○			20	"	3.81	○	○	○	○	○	○		
	9	"	1.43			○			22	"	4.20	○	○	○	○				
	10	"	1.59			○	○		25	"	4.76	○	○	○	○	○	○		
	12	"	1.90			○	○		25	5,000	5.95	○							
	13	"	2.06			○	○		25	6,000	7.14	○							
	15	"	2.38	○	○	○	○	○	30	4,000	5.72	○	○	○	○	○	○		
	16	"	2.54			○	○		30	5,000	7.15	○							
	19	"	3.01	○	○	○	○		30	6,000	8.58	○				○			
	20	"	3.17	○	○	○	○	○	32	4,000	6.08	○	○	○	○	○	○		
	22	"	3.49	○	○	○	○		32	5,000	7.60	○							
	25	"	3.96	○	○	○	○	○	32	6,000	9.12	○							
	30	"	4.76	○	○	○	○	○	35	4,000	6.68	○	○	○	○				
	32	"	5.08	○	○	○	○	○	38	"	7.24	○	○	○	○	○	○		
	34	"	5.40			○	○		38	5,000	9.05	○							
	35	"	5.56	○	○	○	○		38	6,000	10.9	○	○			○			
	38	"	6.04	○	○	○	○	○	40	4,000	7.6	○	○	○	○	○	○		
	40	"	6.36	○	○	○	○	○	40	5,000	9.5	○							
	45	"	7.12	○	○				40	6,000	11.4	○				○			
	50	"	7.92	○	○	○	○	○	42	4,000	8.00				○	○			
	60	"	9.52	○	○	○	○	○	45	"	8.56	○	○	○	○	○	○	○	
	65	"	10.3	○	○	○	○	○	48	"	9.12	○	○	○	○	○			
75	"	11.9	○	○	○	○	○	50	"	9.52	○	○	○	○	○	○	○		
90	"	14.3	○	○	○	○		50	5,000	11.9	○								
100	"	15.8	○	○	○	○	○	50	6,000	14.3	○	○			○				
130	"	20.6			○			60	4,000	11.4	○	○	○	○	○	○	○		
150	"	23.8			○			65	"	12.4	○	○	○	○	○	○	○		
6	9	"	1.71			○			65	5,000	15.4	○							

# SUS304フラットバー 3


SUS304 FB HOT/ COLD/HL/#400研磨



寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400		
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間	スリット
6	65	6,000	18.5	○	○		○		9	22	4,000	6.28	○	○	○	○			
	70	4,000	13.3	○	○	○	○			25	"	7.12	○	○	○	○	○		
	75	"	14.3	○	○	○	○	○		25	6,000	10.7			○				
	75	5,000	17.8	○						30	4,000	8.56	○	○	○	○	○	○	
	75	6,000	21.4	○	○		○			30	6,000	12.8			○				
	90	4,000	17.1	○	○	○	○			32	4,000	9.12	○	○	○	○	○	○	
	100	"	19.0	○	○	○	○	○		32	5,000	11.4	○						
	100	5,000	23.8	○						32	6,000	13.7	○		○				
	100	6,000	28.6	○	○		○			35	4,000	10.0	○		○	○			
	110	4,000	20.9		○	○	○			38	"	10.8	○	○	○	○	○	○	○
	120	"	22.8		○	○	○			38	5,000	13.6	○						
	125	"	23.8		○	○	○			38	6,000	16.3	○		○				
	130	"	24.8		○	○	○			40	4,000	11.4	○	○	○	○	○	○	○
	140	"	26.6		○	○	○			40	5,000	14.2	○						
150	"	28.6		○	○	○		40	6,000	17.1	○		○						
7	20	"	4.44	○				45	4,000	12.8	○	○	○						
8	10	"	2.54			○	○		50	"	14.3	○	○	○	○	○	○		
	16	"	4.08	○		○	○		50	5,000	17.8	○							
	25	"	6.36	○					50	6,000	21.4	○	○	○					
	30	"	7.60	○					55	4,000	15.7	○							
	32	"	8.12	○		○	○	○	60	"	17.1	○	○	○	○	○	○		
	35	"	8.88	○					65	"	18.6	○	○	○	○	○	○		
	38	"	9.64	○		○	○		65	5,000	23.2	○							
	40	"	10.2	○					65	6,000	27.8	○	○	○					
	45	"	11.4	○					75	4,000	21.4	○	○	○	○	○	○		
	50	"	12.7	○		○	○		75	5,000	26.8	○							
	65	"	16.5	○					75	6,000	32.1	○	○	○					
9	75	"	19.0	○					90	4,000	25.7	○	○	○	○				
	100	"	25.4	○					90	5,000	32.1	○							
	13	"	3.71	○		○	○		90	6,000	38.5	○							
	15	"	4.28	○		○	○	○	100	4,000	28.6	○	○	○	○	○	○		
	16	"	4.56	○		○	○		100	5,000	35.7	○							
	19	"	5.44	○		○	○		100	6,000	42.8	○	○	○					
20	"	5.72	○	○	○	○	○	125	4,000	35.7	○		○	○					

# SUS304フラットバー 4


SUS304 FB HOT/ COLD/HL/#400研磨



寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間
9	125	5,000	44.6	○					12	14	4,000	5.32			○			
	125	6,000	53.5	○						15	"	5.72	○					
	150	4,000	42.8	○		○	○			16	"	6.08			○	○		
	150	5,000	53.5	○						19	"	7.24	○		○	○		
	150	6,000	64.2	○						20	"	7.60	○		○	○	○	
	200	4,000	57.2	○		○	○			25	"	9.52	○		○	○	○	
	250	"	71.2	○		○	○			25	6,000	14.3			○			
	300	"	85.6	○		○				30	4,000	11.4	○		○	○	○	
10	15	"	4.76	○		○	○	○	30	6,000	17.1			○				
	19	"	6.04	○		○	○		32	4,000	12.2	○		○	○	○		
	20	"	6.36	○		○	○	○	32	6,000	18.3			○				
	25	"	7.92	○		○	○	○	35	4,000	13.3	○		○				
	30	"	9.52	○		○	○	○	38	"	14.5	○		○	○	○		
	32	"	10.2	○		○	○	○	38	5,000	18.1	○						
	35	"	11.1	○					38	6,000	21.7	○		○				
	38	"	12.0	○		○	○	○	40	4,000	15.2	○		○	○	○		
	40	"	12.7	○		○	○	○	40	6,000	22.9			○				
	45	"	14.3	○					45	4,000	17.1	○						
	50	"	15.8	○		○	○	○	50	"	19.0	○		○	○	○		
	50	5,000	19.8	○					50	5,000	23.8	○						
	50	6,000	23.8	○		○			50	6,000	28.6	○		○				
	60	4,000	19.0	○					65	4,000	24.8	○		○	○	○		
	65	"	20.6	○		○	○	○	65	5,000	31.0	○						
	65	6,000	30.9	○		○			65	6,000	37.1	○		○				
	75	4,000	23.8	○		○	○		70	4,000	26.6	○						
	75	6,000	35.7			○			75	"	28.6	○		○	○	○		
	100	4,000	31.7	○		○	○	○	75	5,000	35.7	○						
	100	5,000	39.6	○					75	6,000	42.8	○		○				
	100	6,000	47.6	○		○			90	4,000	34.2	○		○	○			
	125	4,000	39.6	○		○	○		100	"	38.1	○		○	○	○		
	150	"	47.6	○		○	○		100	5,000	47.6	○						
	200	"	63.6	○		○	○		100	6,000	57.1	○		○				
250	"	79.2	○		○	○		125	4,000	47.6	○		○	○				
300	"	95.2	○					125	5,000	59.5	○							

# SUS304フラットバー 5


SUS304 FB HOT/ COLD/HL/#400研磨



寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間
12	125	6,000	71.4	○					16	150	6,000	114.0	○					
	150	4,000	57.2	○		○	○			200	4,000	102.0	○		○	○		
	150	5,000	71.5	○						250	"	127.0	○		○	○		
	150	6,000	85.8	○						300	"	152.0	○		○			
	200	4,000	76.0	○		○	○			25	"	15.1	○		○	○	○	
	250	"	95.2	○		○	○			30	"	18.1	○					
	300	"	114.0	○		○				32	"	19.3	○		○	○	○	
16	19	"	9.64			○	○		19	35	"	21.1	○					
	20	"	10.2	○		○	○	○		38	"	22.9	○		○	○	○	
	25	"	12.7	○		○	○	○		40	"	24.1	○					
	30	"	15.2	○						45	"	27.1	○					
	32	"	16.2	○		○	○	○		50	"	30.1	○		○	○	○	
	35	"	17.8	○						50	5,000	37.6	○					
	38	"	19.3	○		○	○	○		50	6,000	45.2	○					
	40	"	20.3	○		○	○	○		55	4,000	33.1	○					
	45	"	22.8	○						65	"	39.2	○		○	○		
	50	"	25.4	○		○	○	○		65	5,000	48.9	○					
	50	5,000	31.7	○						65	6,000	58.7	○					
	50	6,000	38.0	○		○				75	4,000	45.2	○		○	○		
	65	4,000	33.0	○		○	○			90	"	54.4	○					
	65	5,000	41.2	○						100	"	60.4	○		○	○		
	65	6,000	49.5	○		○				100	5,000	75.5	○					
	75	4,000	38.1	○		○	○			100	6,000	90.6	○					
	75	5,000	47.6	○						125	4,000	75.2	○		○	○		
	75	6,000	57.1	○		○				150	"	90.4	○		○	○		
	90	4,000	45.6	○						200	"	120.0	○		○	○		
	100	"	50.8	○		○	○			250	"	151.0	○		○	○		
	100	5,000	63.5	○						300	"	181.0	○		○			
	100	6,000	76.2	○		○				20	70	"	44.4	○				
	125	4,000	63.6	○		○	○				22	25	"	17.4	○			
125	5,000	79.5	○					30	"	20.9		○						
125	6,000	95.4	○					32	"	22.3		○		○				
150	4,000	76.0	○		○	○		35	"	24.4		○						
150	5,000	95.0	○					38	"	26.5		○		○				

# SUS304フラットバー 6


SUS304 FB HOT/ COLD/HL/#400研磨



寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間
22	40	4,000	27.9	○					30	250	4,000	238.0	○					
	45	"	31.4	○						300	"	286.0	○					
	50	"	34.9	○		○				35	50	"	55.60	○		○		
	65	"	45.2	○		○			65		"	72.00	○		○			
	75	"	52.4	○		○			75		"	83.20	○		○			
	90	"	62.8	○					100		"	111.0	○		○			
	100	"	69.6	○		○			125		"	139.0	○					
	125	"	87.2	○					150		"	166.0	○					
	150	"	105.0	○					40	50	"	63.60	○					
	200	"	140.0	○						65	"	82.40	○					
	250	"	174.0	○						75	"	95.20	○					
	300	"	209.0	○						100	"	127.0	○					
25	32	"	25.4	○		○				125	"	158.0	○					
	38	"	30.1	○		○				150	"	190.0	○					
	40	"	31.7	○					50	65	"	103.0	○					
	45	"	35.7	○				65		"	119.0	○						
	50	"	39.6	○		○				100	"	158.0	○					
	60	"	47.6	○				125		"	198.0	○						
	65	"	51.6	○		○		150		"	238.0	○						
	75	"	59.6	○		○		60		75	"	143.0	○					
	100	"	79.2	○		○			100	"	190.0	○						
	125	"	99.2	○		○			125	"	238.0	○						
	150	"	119.0	○		○			150	"	286.0	○						
	200	"	158.0	○		○			65	75	"	155.0	○					
250	"	198.0	○				70		100	"	222.0	○						
300	"	238.0	○					125	"	278.0	○							
30	50	"	47.6	○		○			150	"	333.0	○						
	55	"	52.4	○		○		80	100	"	254.0	○						
	65	"	62.0	○		○			125	"	317.0	○						
	75	"	71.2	○		○			150	"	381.0	○						
	100	"	95.2	○		○		90	125	"	357.0	○						
	125	"	119.0	○					150	"	428.0	○						
	150	"	143.0	○				100	125	"	396.0	○						
	200	"	190.0	○					150	"	476.0	○						

# ステンレス六角棒(冷間引抜)

SUS304/SUS303




SUS304			SUS303		
寸 法 mm		1本の質量 (kg/本)	寸 法 mm		1本の質量 (kg/本)
対辺 A	定尺長さ		対辺 A	定尺長さ	
5	2,000	0.344	5	2,100	0.361
6	"	0.494	6	"	0.519
7	"	0.674	7	"	0.708
8	4,000	1.76	8	4,100	1.80
9	"	2.22	9	"	2.28
10	"	2.75	10	"	2.82
11	"	3.32	11	"	3.41
12	"	3.97	12	"	4.05
13	"	4.64	13	"	4.76
14	"	5.40	14	"	5.54
17	"	7.92	17	"	8.12
19	"	9.92	19	"	10.20
21	"	12.10	21	"	12.40
22	"	13.3	23	"	14.9
23	"	14.5	24	"	16.2
24	"	15.8	26	"	19.0
26	"	18.6	27	"	20.5
27	"	20.0	29	"	23.7
29	"	23.1			
30	"	24.7			
32	"	28.1			
35	"	33.6			
36	"	35.6			
38	"	39.7			
41	"	46.0			
46	"	58.0			
50	"	68.8			

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

# ステンレス丸棒 1

SUS303/304/316




直径 D mm	303 304 1mの質量 (kg/m)	酸	H	ピー		直			引		セン		
		洗	L	リング	リング	棒			抜		タ		
		304	304	304	303	304	303	316	304	303	304	303	
		4m	4m	ロング	ロング	2m	4m	2m	2m	ロング	ロング	2m	2.1m
2	0.025					○						○	
2.5	0.039					○						○	
3	0.056					○		○				○	○
3.5	0.076					○						○	
4	0.100					○	○	○	○			○	○
4.5	0.126											○	
5	0.156					○	○	○	○			○	○
6	0.224					○	○	○	○			○	○
7	0.305					○	○	○	○			○	○
8	0.399	○	○			○	○	○	○			○	○
	0.402			○									
9	0.504	○	○			○	○	○	○			○	○
	0.508			○									
10	0.623	○	○			○	○	○	○			○	○
	0.627			○									
11	0.754											○	○
	0.754			○									
12	0.897	○	○			○	○		○			○	○
	0.908			○									
13	1.05	○	○			○	○			○	○	○	○
	1.06			○	○								
14	1.22	○	○							○	○	○	○
	1.23			○									
15	1.40	○	○							○	○	○	○
	1.42			○									
16	1.59	○	○							○	○	○	○
	1.61			○	○								
17	1.80									○		○	○
	1.82			○									
18	2.02	○	○							○	○	○	○
	2.03			○									
19	2.25	○	○							○	○	○	○
	2.27			○	○								
20	2.49	○	○							○	○	○	○
	2.51			○	○								

表記の質量はテーブル質量です。実際の商品とは異なる場合があります



# ステンレス丸棒 2

SUS303/304/316




直径 D mm	303 304 1mの質量 (kg/m)	酸洗	H L 丸 棒	ピー リ ン グ		直 棒				引 抜		セ ン タ レ ス	
		304	304	304	303	304		303	316	304	303	304	303
		4m	4m	ロング	ロング	2m	4m	2m	2m	ロング	ロング	2m	2.1m
22	3.01	○	○							○	○	○	○
	3.04			○	○								
23	3.29											○	○
	3.33			○									
24	3.59											○	○
	3.61			○									
25	3.89	○	○							○	○	○	○
	3.92			○	○								
26	4.21											○	
	4.25			○									
28	4.88	○	○							○	○	○	○
	4.93			○	○								
30	5.61	○	○							○	○	○	○
	5.65			○	○								
32	6.38									○	○	○	○
	6.43			○	○								
34	7.25			○									
35	7.63									○	○	○	○
	7.68			○	○								
36	8.13			○	○								
38	8.99									○		○	○
	9.06			○	○								
40	9.97									○	○	○	○
	10.0			○	○								
42	11.0									○			
	11.1			○	○								
44	12.1			○									
45	12.6									○		○	
	12.7			○	○								
46	13.3			○	○								
48	14.3									○			
	14.4			○	○								
50	15.6									○	○	○	
	15.6			○	○								

表記の質量はテーブル質量です。実際の商品とは異なる場合があります

# ステンレス丸棒 3

SUS303/304/316



直径 D mm	303 304 1mの質量 (kg/m)	酸洗	H L 丸 棒	ピー リ ン グ		直 棒				引 抜		セ ン タ レ ス	
		304	304	304	303	304		303	316	304	303	304	303
		4m	4m	ロング	ロング	2m	4m	2m	2m	ロング	ロング	2m	2.1m
55	18.8									○			
	18.9			○	○								
60	22.4									○			
	22.5			○	○								
65	26.3									○			
	26.4			○	○								
70	30.6			○	○								
75	35.2			○	○								
80	40.0			○	○								
85	45.3			○	○								
90	50.7			○	○								
95	56.5			○	○								
100	62.6			○	○								
105	69.0			○									
110	75.7			○									
115	82.7			○									
120	90.1			○									
125	97.7			○									
130	106.0			○									
135	114.0			○									
140	123.0			○									
150	141.0			○									
155	152.0			○									
160	161.0			○									
170	182.0			○									
180	204.0			○									
190	227.0			○									
200	252.0			○									
210	277.0			○									
220	304.0			○									
230	332.0			○									
240	362.0			○									
250	392.0			○									

表記の質量はテーブル質量です。実際の商品とは異なる場合があります