


SUS304フラットバー 1

SUS304 FB HOT・COLD・HL・#400研磨




● 在庫品

寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間
2	6	2,000	0.190			●			3	38	4,000	3.62	●	●	●	●	●	
	8	"	0.254			●				40	"	3.81	●	●	●	●	●	●
	9	"	0.286			●				42	"	4.00			●	●		
	10	"	0.318			●				45	"	4.28	●	●	●	●		
	10	3,000	0.477		●	●				48	"	4.56			●	●		
	10	4,000	0.636		●	●	●			50	"	4.76	●	●	●	●	●	●
	12	"	0.760			●				60	"	5.72	●	●	●	●	●	●
	15	"	0.952		●	●	●			65	"	6.20	●	●	●	●		
	20	"	1.27		●	●	●			75	"	7.12		●	●	●	●	●
	25	"	1.59		●	●	●			90	"	8.56			●			
	30	"	1.90		●	●	●			100	"	9.52		●	●	●	●	●
	32	"	2.03		●	●	●			110	"	10.5			●			
	35	"	2.22		●					120	"	11.4			●			
	38	"	2.41		●	●				125	"	11.9			●			
	40	"	2.54		●	●	●			130	"	12.4			●			
	45	"	2.86		●	●	●			140	"	13.3			●			
50	"	3.17		●	●	●		150	"	14.3			●					
3	5	3,000	0.357			●			4	9	"	1.14			●			
	6	4,000	0.568			●				10	"	1.27			●	●		
	7	"	0.668			●				11	"	1.40		●	●	●		
	8	"	0.760			●				12	"	1.52			●			
	9	"	0.856			●				13	"	1.65		●	●	●		
	10	"	0.952		●	●	●			15	"	1.90	●	●	●	●	●	
	12	"	1.14		●	●	●			16	"	2.03	●	●	●	●		
	13	"	1.24		●	●	●			17	"	2.16			●			
	15	"	1.43	●	●	●	●	●		19	"	2.41	●	●	●	●		
	16	"	1.52		●	●	●			20	"	2.54	●	●	●	●	●	
	19	"	1.81	●	●	●	●			22	"	2.79	●	●	●	●		
	20	"	1.90	●	●	●	●	●		25	"	3.17	●	●	●	●	●	
	22	"	2.09		●	●	●			30	"	3.81	●	●	●	●	●	
	25	"	2.38	●	●	●	●	●		32	"	4.08	●	●	●	●	●	
	30	"	2.86	●	●	●	●	●		35	"	4.44	●	●	●	●		
	32	"	3.04	●	●	●	●	●		38	"	4.84	●	●	●	●	●	
35	"	3.33	●	●	●	●		40	"	5.08	●	●	●	●	●			

SUS304フラットバー 2

SUS304 FB HOT・COLD・HL・#400研磨




● 在庫品

寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間
4	45	4,000	5.72	●	●	●	●		6	10	4,000	1.90			●	●		
	50	"	6.36	●	●	●	●	●		12	"	2.28			●	●		
	60	"	7.60	●	●	●	●	●		13	"	2.48			●	●		
	65	"	8.24	●	●	●	●	●		15	"	2.86	●	●	●	●	●	●
	75	"	9.52	●	●	●	●	●		16	"	3.04			●	●		
	90	"	11.4			●	●			18	"	3.42			●	●		
	100	"	12.7		●	●	●	●		19	"	3.62	●	●	●	●		
5	8	"	1.27			●			20	"	3.81	●	●	●	●	●	●	
	9	"	1.43			●			22	"	4.20	●	●	●	●			
	10	"	1.59			●	●		25	"	4.76	●	●	●	●	●	●	
	12	"	1.90			●	●		25	5,000	5.95	●						
	13	"	2.06			●	●		25	6,000	7.14	●						
	15	"	2.38	●	●	●	●	●	30	4,000	5.72	●	●	●	●	●	●	
	16	"	2.54			●	●		30	5,000	7.15	●						
	19	"	3.01	●	●	●	●		30	6,000	8.58	●			●			
	20	"	3.17	●	●	●	●	●	32	4,000	6.08	●	●	●	●	●	●	
	22	"	3.49	●	●	●	●		32	5,000	7.60	●						
	25	"	3.96	●	●	●	●	●	32	6,000	9.12	●						
	30	"	4.76	●	●	●	●	●	35	4,000	6.68	●	●	●	●			
	32	"	5.08	●	●	●	●	●	38	"	7.24	●	●	●	●	●	●	
	34	"	5.40			●	●		38	5,000	9.05	●						
	35	"	5.56	●	●	●	●		38	6,000	10.9	●			●			
	38	"	6.04	●	●	●	●	●	40	4,000	7.6	●	●	●	●	●	●	
	40	"	6.36	●	●	●	●	●	40	5,000	9.5	●						
	45	"	7.12	●	●				40	6,000	11.4	●			●			
	50	"	7.92	●	●	●	●	●	42	4,000	8.00			●	●			
	60	"	9.52	●	●	●	●	●	45	"	8.56	●	●	●	●	●	●	
65	"	10.3	●	●	●	●	●	48	"	9.12	●	●	●	●				
75	"	11.9	●	●	●	●	●	50	"	9.52	●	●	●	●	●	●		
90	"	14.3	●	●	●	●		50	5,000	11.9	●							
100	"	15.8	●	●	●	●	●	50	6,000	14.3	●	●		●				
130	"	20.6			●			60	4,000	11.4	●	●	●	●	●	●		
150	"	23.8			●			65	"	12.4	●	●	●	●	●	●		
6	9	"	1.71			●			65	5,000	15.4	●						

SUS304フラットバー 3

SUS304 FB HOT・COLD・HL・#400研磨




● 在庫品

寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間
6	65	6,000	18.5	●			●		9	22	4,000	6.28	●		●	●		
	70	4,000	13.3	●	●	●	●			25	"	7.12	●		●	●	●	
	75	"	14.3	●	●	●	●	●		25	6,000	10.7			●			
	75	5,000	17.8	●						30	4,000	8.56	●		●	●	●	
	75	6,000	21.4	●			●			30	6,000	12.8			●			
	90	4,000	17.1	●	●	●	●			32	4,000	9.12	●		●	●	●	
	100	"	19.0	●	●	●	●	●		32	5,000	11.4	●					
	100	5,000	23.8	●						32	6,000	13.7	●		●			
	100	6,000	28.6	●			●			35	4,000	10.0	●		●	●		
	110	4,000	20.9		●	●	●			38	"	10.8	●		●	●	●	
	120	"	22.8		●	●	●			38	5,000	13.6	●					
	125	"	23.8		●	●	●			38	6,000	16.3	●		●			
	130	"	24.8		●	●	●			40	4,000	11.4	●		●	●	●	
	140	"	26.6		●	●	●			40	5,000	14.2	●					
	150	"	28.6		●	●	●			40	6,000	17.1	●		●			
7	20	"	4.44	●					45	4,000	12.8	●		●				
8	10	"	2.54			●	●		50	"	14.3	●		●	●	●		
	16	"	4.08	●		●	●		50	5,000	17.8	●						
	25	"	6.36	●					50	6,000	21.4	●		●				
	30	"	7.60	●					55	4,000	15.7	●						
	32	"	8.12	●		●	●	●	60	"	17.1	●		●	●	●		
	35	"	8.88	●					65	"	18.6	●		●	●	●		
	38	"	9.64	●		●	●		65	5,000	23.2	●						
	40	"	10.2	●					65	6,000	27.8	●		●				
	45	"	11.4	●					75	4,000	21.4	●		●	●	●		
	50	"	12.7	●		●	●		75	5,000	26.8	●						
	65	"	16.5	●					75	6,000	32.1	●		●				
9	13	"	3.71	●		●	●		90	4,000	25.7	●		●	●			
	15	"	4.28	●		●	●	●	90	5,000	32.1	●						
	16	"	4.56	●		●	●		90	6,000	38.5	●						
	19	"	5.44	●		●	●		100	4,000	28.6	●		●	●	●		
	20	"	5.72	●		●	●	●	100	5,000	35.7	●						
									100	6,000	42.8	●		●				
								125	4,000	35.7	●		●	●				

SUS304フラットバー 4

SUS304 FB HOT・COLD・HL・#400研磨




● 在庫品

寸法 mm	1本の質量 (kg/本)		HOT		COLD	HL	#400	寸法 mm	1本の質量 (kg/本)		HOT		COLD	HL	#400	
	厚さA	幅 B	定尺長さ	熱間					スリット	厚さA	幅 B	定尺長さ				熱間
9	125	5,000	44.6	●					14	4,000	5.32			●		
	125	6,000	53.5	●					15	"	5.72	●				
	150	4,000	42.8	●		●	●		16	"	6.08			●	●	
	150	5,000	53.5	●					19	"	7.24	●		●	●	
	150	6,000	64.2	●					20	"	7.60	●		●	●	●
	200	4,000	57.2	●		●	●		25	"	9.52	●		●	●	●
	250	"	71.2	●		●	●		25	6,000	14.3			●		
	300	"	85.6	●		●			30	4,000	11.4	●		●	●	●
10	15	"	4.76	●		●	●	●	30	6,000	17.1			●		
	19	"	6.04	●		●	●		32	4,000	12.2	●		●	●	●
	20	"	6.36	●		●	●	●	32	6,000	18.3			●		
	25	"	7.92	●		●	●	●	35	4,000	13.3	●		●		
	30	"	9.52	●		●	●	●	38	"	14.5	●		●	●	●
	32	"	10.2	●		●	●	●	38	5,000	18.1	●				
	35	"	11.1	●					38	6,000	21.7	●		●		
	38	"	12.0	●		●	●	●	40	4,000	15.2	●		●	●	●
	40	"	12.7	●		●	●	●	40	6,000	22.9			●		
	45	"	14.3	●					45	4,000	17.1	●				
	50	"	15.8	●		●	●	●	50	"	19.0	●		●	●	●
	50	5,000	19.8	●					50	5,000	23.8	●				
	50	6,000	23.8	●		●			50	6,000	28.6	●		●		
	60	4,000	19.0	●					65	4,000	24.8	●		●	●	●
	65	"	20.6	●		●	●	●	65	5,000	31.0	●				
	65	6,000	30.9			●			65	6,000	37.1	●		●		
	75	4,000	23.8	●		●	●		70	4,000	26.6	●				
	75	6,000	35.7			●			75	"	28.6	●		●	●	●
	100	4,000	31.7	●		●	●	●	75	5,000	35.7	●				
	100	5,000	39.6	●					75	6,000	42.8	●		●		
100	6,000	47.6	●		●			90	4,000	34.2	●		●	●		
125	4,000	39.6	●		●	●		100	"	38.1	●		●	●	●	
150	"	47.6	●		●	●		100	5,000	47.6	●					
200	"	63.6	●		●	●		100	6,000	57.1	●		●			
250	"	79.2	●		●	●		125	4,000	47.6	●		●	●		
300	"	95.2	●					125	5,000	59.5	●					

SUS304フラットバー 5

SUS304 FB HOT・COLD・HL・#400研磨




● 在庫品

寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ				熱間
12	125	6,000	71.4	●					16	150	6,000	114.0	●					
	150	4,000	57.2	●		●	●			200	4,000	102.0	●		●	●		
	150	5,000	71.5	●						250	"	127.0	●		●	●		
	150	6,000	85.8	●						300	"	152.0	●		●			
	200	4,000	76.0	●		●	●			19	25	"	15.1	●		●	●	●
	250	"	95.2	●		●	●				30	"	18.1	●				
	300	"	114.0	●		●					32	"	19.3	●		●	●	●
16	19	"	9.64			●	●		35		"	21.1	●					
	20	"	10.2	●		●	●	●	38		"	22.9	●		●	●	●	
	25	"	12.7	●		●	●	●	40		"	24.1	●					
	30	"	15.2	●					45		"	27.1	●					
	32	"	16.2	●		●	●	●	50		"	30.1	●		●	●	●	
	35	"	17.8	●					50		5,000	37.6	●					
	38	"	19.3	●		●	●	●	50		6,000	45.2	●					
	40	"	20.3	●		●	●	●	55		4,000	33.1	●					
	45	"	22.8	●					65		"	39.2	●		●	●		
	50	"	25.4	●		●	●	●	65		5,000	48.9	●					
	50	5,000	31.7	●					65	6,000	58.7	●						
	50	6,000	38.0	●		●			75	4,000	45.2	●		●	●			
	65	4,000	33.0	●		●	●		90	"	54.4	●						
	65	5,000	41.2	●					100	"	60.4	●		●	●			
	65	6,000	49.5	●		●			100	5,000	75.5	●						
	75	4,000	38.1	●		●	●		100	6,000	90.6	●						
	75	5,000	47.6	●					125	4,000	75.2	●		●	●			
	75	6,000	57.1	●		●			150	"	90.4	●		●	●			
	90	4,000	45.6	●					200	"	120.0	●		●	●			
	100	"	50.8	●		●	●		250	"	151.0	●		●	●			
	100	5,000	63.5	●					300	"	181.0	●		●				
	100	6,000	76.2	●		●			20	70	"	44.4	●					
	125	4,000	63.6	●		●	●			22	25	"	17.4	●				
125	5,000	79.5	●					30			"	20.9	●					
125	6,000	95.4	●					32			"	22.3	●		●			
150	4,000	76.0	●		●	●		35			"	24.4	●					
150	5,000	95.0	●					38	"		26.5	●		●				

SUS304フラットバー 6

SUS304 FB HOT・COLD・HL・#400研磨




● 在庫品

寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400	寸法 mm			1本の質量 (kg/本)	HOT		COLD	HL	#400
厚さA	幅 B	定尺長さ		熱間	スリット				熱間	スリット	厚さA		幅 B	定尺長さ			
22	40	4,000	27.9	●					30	250	4,000	238.0	●				
	45	"	31.4	●						300	"	286.0	●				
	50	"	34.9	●		●			35	50	"	55.60	●		●		
	65	"	45.2	●		●				65	"	72.00	●		●		
	75	"	52.4	●		●				75	"	83.20	●		●		
	90	"	62.8	●						100	"	111.0	●		●		
	100	"	69.6	●		●				125	"	139.0	●				
	125	"	87.2	●					150	"	166.0	●					
	150	"	105.0	●					40	50	"	63.60	●				
	200	"	140.0	●						65	"	82.40	●				
	250	"	174.0	●						75	"	95.20	●				
	300	"	209.0	●						100	"	127.0	●				
								125		"	158.0	●					
25	32	"	25.4	●		●			50	150	"	190.0	●				
	38	"	30.1	●		●				65	"	103.0	●				
	40	"	31.7	●						75	"	119.0	●				
	45	"	35.7	●						100	"	158.0	●				
	50	"	39.6	●		●				125	"	198.0	●				
	60	"	47.6	●					150	"	238.0	●					
	65	"	51.6	●		●			60	75	"	143.0	●				
	75	"	59.6	●		●				100	"	190.0	●				
	100	"	79.2	●		●				125	"	238.0	●				
	125	"	99.2	●		●				150	"	286.0	●				
	150	"	119.0	●		●			65	75	"	155.0	●				
	200	"	158.0	●		●			70	100	"	222.0	●				
250	"	198.0	●					125		"	278.0	●					
300	"	238.0	●					150		"	333.0	●					
30	50	"	47.6	●		●			80	100	"	254.0	●				
	55	"	52.4	●		●				125	"	317.0	●				
	65	"	62.0	●		●				150	"	381.0	●				
	75	"	71.2	●		●			90	125	"	357.0	●				
	100	"	95.2	●		●				150	"	428.0	●				
	125	"	119.0	●					100	125	"	396.0	●				
	150	"	143.0	●						150	"	476.0	●				
	200	"	190.0	●													

SUS316,316Lフラットバー

SUS316・316L FB HOT



寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)
厚さ A	幅 B	定尺長さ		厚さ A	幅 B	定尺長さ	
3	20	4,000	1.92	9	90	4,000	25.8
	25	"	2.39		100	"	28.7
	30	"	2.87	10	50	"	16.0
	32	"	3.06		100	"	31.9
	38	"	3.64	12	25	"	9.6
	40	"	3.83		32	"	12.2
	50	"	4.80		38	"	14.6
4	25	"	3.19		50	"	19.2
	30	"	3.83		65	"	24.9
	40	"	5.12	75	"	28.7	
	50	"	6.40	100	"	38.3	
5	20	"	3.19	16	25	"	12.8
	25	"	3.99		32	"	16.4
	30	"	4.80		38	"	19.4
	32	"	5.12		50	"	25.5
	38	"	6.08		65	"	33.2
	40	"	6.40		75	"	38.3
	50	"	8.00		100	"	51.2
6	25	"	4.80	19	50	"	30.3
	30	"	5.76		65	"	39.4
	32	"	6.12		75	"	45.6
	38	"	7.28		100	"	60.8
	40	"	7.68				
	50	"	9.56				
	65	"	12.4				
	75	"	14.4				
	100	"	19.2				
9	25	"	7.2				
	30	"	8.6				
	32	"	9.2				
	38	"	10.9				
	50	"	14.4				
	65	"	18.7				
	75	"	21.6				

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。重量を表示している規格は標準在庫品です。

SUS303フラットバー

SUS303 FB HOT



寸法 mm			1本の質量 (kg/本)	寸法 mm			1本の質量 (kg/本)
厚さ A	幅 B	定尺長さ		厚さ A	幅 B	定尺長さ	
6	25	4,000	4.76	19	40	4,000	24.1
	30	"	5.72		50	"	30.1
	40	"	7.60		65	"	39.2
	50	"	9.52		75	"	45.2
	65	"	12.4		100	"	60.4
	75	"	14.3		150	"	90.4
	100	"	19.0		200	"	120.0
9	25	"	7.12	22	25	"	17.4
	30	"	8.56		30	"	20.9
	40	"	11.4		40	"	27.9
	50	"	14.3		50	"	34.9
	65	"	18.6		65	"	45.2
	75	"	21.4		75	"	52.4
	100	"	28.6		100	"	69.6
12	25	"	9.52	25	150	"	105.0
	30	"	11.4		200	"	140.0
	40	"	15.2		30	50	"
	50	"	19.0	65		"	51.6
	65	"	24.8	75		"	59.6
	75	"	28.6	100		"	79.2
	100	"	38.1	150		"	119.0
	150	"	57.2	200	"	158.0	
200	"	76.0	35	50	"	55.6	
16	25	"		12.7	75	"	83.2
	30	"		15.2	100	"	111.0
	40	"		20.3	40	50	"
	50	"	25.4	75		"	95.2
	65	"	33.0	100		"	127.0
	75	"	38.1	50	75	"	119.0
	100	"	50.8		19	25	"
	150	"	76.0	30		"	18.1
	200	"	102.0				

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。重量を表示している規格は標準在庫品です。